

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 & 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5770)

-
- Set a post, cor. of secs. 16, 17, 20 and 21, from which
- A B.Oak 24" dia., bears N.45°W., 75 lks. dist.
 - A B.Oak 14" dia., bears S.24°W., 82 lks. dist.
 - A B.Oak 36" dia., bears N.49°E., 128 lks. dist.
 - A B.Oak 8" dia., bears S.29°E., 125 lks. dist.

Wm. C. Stiles, Seek, Inc. - For: L & H Lumber Co. - March 23, 1967 - C.S. File 55/32 and M 32-76

-
- Established by double proportionate measurement.
- Set - 1½" Galv. I.P., from which
- 12" Oak scribed S 16 BT bears N.33°08'59"E., 9.5 ft.
 - 12" Oak scribed S17 BT bears N.77°36'41"W., 31.7 ft.
 - "X" chiseled in a rock face bears S.47°31'01"E., 33.34 ft.
 - "X" chiseled in a rock face bears S.31°44'29"W., 43.8 ft.
- See Map 32-76 for bearing and dist. to other corners.

Glenn Baughman, L.S. #356 - For: Glide Lumber Products - June 1984 - RM 3-62; C.S. File 58/144

-
- Found - 1" I. pipe.
- 11" W.Oak N.77½°W., 31.7 ft. (healed blaze.)
 - 13" Oak N.33°E., 9.5 ft. mkd. as per M 32-76.
- Set - 5/8" x 30" I.Rod mkd. "Baughman Tech. Serv."
- BTs - 26" D.Fir N.10 3/4°E., 192.2 ft. scribed "T28S R7W S16 BT".
- 11" W.Oak S.69 3/4°E., 15.7 ft. scribed "T28S R7W S21 BT".
 - 11" W.Oak S.53¼°W., 16.4 ft.
 - 15" D.Fir N.65½°W., 63.5 ft. scribed "T28S R7W S17 BT".
- Set I.P. bears N.46°15'18"W., 24.86 ft. from found I.Pipe.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20012-3)

-
- The cor. of secs. 16, 17, 20 & 21, reestablished by Baughman, in 1984, and is accepted as the corner; monumented with an iron rod, 5/8" diam., firmly set, projecting 4" above ground, with plastic cap mkd. BAUGHMAN TECH SERV, from which bearing trees mkd. by Baughman:
- A fir, 29" diam., bears N. 10¼° E., 291 lks., with fragmentary scribe marks visible on partially healed double blaze.
- continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An oak, 11" diam., bears S.69½° E., 24 lks., with fragmentary scribe marks visible on partially healed double blaze.

An oak, 11" diam., bears S.53¼°W., 25 lks., with fragmentary scribe marks visible on partially healed double blaze. This tree is Stiles' SW. bearing tree and was also scribed and used by Baughman.

A fir, 15" diam., bears N.65¼°W., 95 lks., with fragmentary scribe marks visible on partially healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, directly over the iron rod, with brass cap mkd.

T28S R7W
S17 | S16
S20 | S21
1992

No new accessories.

The corner is located South, 0.02 chs. dist., of a seasonal creek.

From this point, a point established as the cor. of secs. 16, 17, 20 & 21 by Stiles, in 1967, bears S.46°32'30"E., 0.384 chs.; monumented with an iron pipe, 1½" diam., firmly set, projecting 4" above ground, from which accessories mkd. by Stiles:

An oak, 13" diam., bears N.34½°E., 15 lks., with healed blaze.

A 4" high "X" chiseled in a rock face, bears S.47°E., 50 lks.

A 4" high "X" chiseled in a rock face, bears S.32½°W., 53 lks.

An oak, 11" diam., bears N.77°W., 48 lks., with healed blaze. This tree was also scribed and used by Baughman and contains 2 sets of blazes and scribes.

Fd. a copper rod, 5/8" diam., buried alongside the iron pipe. This corner was rejected due to erroneous position and was not used in this survey.

Fd. Ok by G. Lang, 4/2008 - M158-39