

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 and 17

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5771)

-----  
Set quar. sec. post, from which  
A B.Oak 6" dia., bears S.80°W., 50 lks.  
A W.Oak 8" dia., bears S.88°W., 160 lks.

Wm. C. Stiles, Seek, Inc. - For: L & H Lumber Co. - March 23, 1967 - C.S. File 55/32; M 32-76

-----  
Established by single proportionate measurement, N.1°37'37"E. 2558.14 ft. from cor. to secs. 16, 27, 20 and 21.  
Set - 1½" Galv. I.Pipe, from which  
24" Oak bears N.88°28'03"E., 33.8 ft. scribed ¼ S16BT  
16" Oak bears S.51°00'45"W., 40.0 ft. scribed ¼ S17 BT

Glenn Baughman, L.S. #536 - For: Glide Lumber Products - June 1984 - RM 3-62; C.S. File 58/114

-----  
Found - 1" I.Pipe.  
24" W.Oak S.88½°E., 33.8 ft.  
19" W.Oak S.51°W., 40.0 ft. mkd. as per M 32-76  
Set - 5/8" x 30" Iron rod mkd. "Baughman Tech. Serv."  
New BTs -24" W.Oak S.78 3/4°E., 34.8 ft., scribe visible.  
19" W.Oak S.41 3/4°W., 44.2 ft., scribe visible.  
Set monument bears N.4°38'13"W., 7.77 ft. from found I.P.

Fd. Ok by G. Lang, 4/2008 - M158-39