

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5771)

Set a post, cor. of secs. 8, 9, 16 and 17, from which
A B.Oak 7" dia., bears S.63°E., 60 lks. dist.
A Laurel 15" dia., bears N.65°E., 110 lks. dist.
A Laurel 18" dia., bears N.35°W., 87 lks. dist.
A B.Oak 18" dia., bears S.60°W., 8 lks. dist.

Doug. County Surveyors Office - John M. Powell and crew -
Dec. 2, 1966 - C.S. File 52/79-1

Found - GLO 1924 Brass cap, properly marked. (See Mensch survey, GLO notes, Vol. 14 Pg. 5892 for his recorded "tie" to this corner.)
Orig. 7" B.Oak, now down, S.63°E., 39.6 ft.
Orig. 15" now 36" Laurel, N.65°E., 72.6 ft. (Rec. N.63°E.)
Orig. 18" now 32" Laurel, N.35°W., 57.4 ft.
Orig. 18" B.Oak, now down, S.60°W., 5.3 ft.
23" D.Fir S.44°E., 16.5 ft., shows good scar.
24" D.Fir S.82°W., 27.4 ft. shows good scar.
20" D.Fir N.39°W., 20.2 ft. shows good scar.
9" D.Fir N.51°E., 21.4 ft. opened for scribe "W S9".
face rotten, ring count places scribe 1924.
New BT - 16" D.Fir N.73°E., scribed T28S R7W S9 CS BT.
This corner on old E-W fence line.

BLM resurvey by James E. Jelley under Group #878 - Survey, July/Aug. 1975 - (DCSO records, Vol. 37 Page 15420)

The Sec. cor., rehabilitated by Fred Mensch, Cadastral Engineer, in 1924, and not of record, monumented with an iron post, 2" dia., firmly set, projecting 6" above ground with marked brass cap.
from which the remains of the orig. bearing trees:
A Madrone 32" dia., bears N.57¼°E., 100 lks. dist., no marks visible on decayed blaze. (Rec. N.65°E., 110 lks.)
A root hole bears S.60°W., 8 lks. with a down B.Oak alongside, 36" dia., no marks visible.
A Madrone 30", bears N.36¼°W., 87 lks., no marks visible on decayed blaze. (Rec. N.35°W.)
and bearing trees mkd. by Mensch:
A Fir 11" dia., bears N.51°E., 32 lks., with scribe marks 7W S visible on open blaze.
A Fir 25" dia., bears S.42°E., 24 lks. with healed blaze.
A Fir 26" dia., S.84°W., 42 lks. with healed blaze.
A Fir 28" dia., N.39 3/4°W., 31 lks. with healed blaze.

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. 8, 9, 16 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a bearing tree of which I have no record:
A Fir 20" dia., bears N.74°E., 37½ lks. dist., with
healed blaze. (This is probably DCSO BT from 1966. v1)
Add marks 1975 to brass cap.

BLM resurvey by Bishop and Rogers, under Group #1124 - Survey
April 1983/Jan. 1984 (DCSO records, Vol. 46 Page 17750)

The Cor. determined at record bearing and dist. from the
remaining original bearing tree

A Madrone 36" dia., bears N.57¼°E., 100 lks. dist., no
marks visible on partially opened blaze.

and the remains of bearing trees mkd. by Mensch

A Fir 8" dia., bears N.51°E., 32 lks. dist., with a
healed single blaze.

A sawed Fir stump 26" dia., bears S.42°E., 24 lks. dist.,
with S16 visible on a cut open blaze.

A Fir 28" dia., bears S.84°W., 42 lks. dist., with a
healed blaze.

A Fir 24" dia., bears N.39¼°W., 31 lks. with healed face.
and bearing tree recorded by Jelley

A Fir 20" dia., bears N.74°E., 37½ lks. dist., with a
healed blaze.

At the corner point

Set an alum. post, 28" long 2½" dia., 24" in the ground, with
alum. cap mkd.

T 28 S	R 7 W
S 8	S 9
S 17	S 16
1983	

from which a new bearing tree

A Fir 6" dia., bears S.40½°E., 241 lks. dist.,
mkd. T28S R7W S16 BT.

Fd. OK, Glenn Baughman, July 1984, RM 3-62

Fd. OK by Virgil Broadwater, Sept. 1996 - M 126-18

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch
& Crew - For: US Department of Interior, BLM - Petty Larsony
- Task E - March 2023 - M185-3 A-D

Found - ¾" Aluminum cap, 0.3' above ground from which:

A barb wire fence corner running south & west bears
Northeast 2.2'

A Madrone 36' dia., bears N.30°W., 56.6' partial
healed blaze (1854)

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Bishop and Rogers in 1984 found A 36" Madrone to Northeast, however no Madrone trees were found to Northeast during this survey we believe the 36" Madrone tree found this survey to be original.

A stump 20" dia. (3' high), bears N.32°W., 20.2' with BT sign (1966)

A stump 10" dia. (3.5' high), bears N.52°W., 22.0' with partially healed blaze and rotted scribed marks visible (1924)

A stump 18" dia. (3.5' high), bears N.73°E., 25.1' with BT sign (1966)

Note - C.S file 52/79-1 no record distance to N.73°E., BT existing sign on 18" stump MKD: S.73°W., 25.1' 12-2-66

We set a chaining nail at 25.1' to match original BT sign.

A rotted stump 32" dia. (2' high), bears S.42°E., 15.8' (1924)

A stump 34" dia., bears S.82°W., 27.4' with BT sign (1924)

(Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)

Established the following -

A 7" Fir dia. bears N.32°E. 17.4' mkd: T28S R7W S9 BT

A 8" Fir dia. bears S.80°E. 6.0' mkd: T28S R7W S16 BT

(Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BTs)