

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5772)

-----  
Set quar sec. post, from which  
A B.Oak 30" dia., bears S.20°E., 150 lks.  
A B.Oak 7" dia., bears S.25°W., 165 lks.

Claude Kerr - Feb. 1953 - C.S. File 41/120

-----  
A 3 x 4" Cedar stake was set by proportional measure. (2567.1 ft.)  
A 12" Cedar N.70°E., 11.6 ft. mkd. ¼ S BT.  
A 12" Laurel, S.76°W., 26.6 ft.

Doug. County Surveyors Office - James Byron - Milo Godfrey; & Clete Putnam - Feb./March 1961 - C.S. File 49/50-37

-----  
Found both BTs as recorded by Kerr, 1953  
Set Brass cap at cor. mkd: County Surveyor's Office, 1961  
¼ S8 | S9 T28S R7W

Fd. OK, BLM resurvey by Bishop & Rogers, April 1983/Jan. 1984 (DCSO records, Vol. 46 Page 17751)

Fd. OK by Virgil Broadwater, Sept. 1996 - M 126-18

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Petty Larsony - Task E - March 2023 - M185-3 A-D

-----  
Found - 2½" brass cap, 0.7' above ground from which:  
A Cedar stump 30" dia. (2' high), bears N.80°E., 12.2' (1984)  
A Madrone stump 28" dia. (2' high), bears S.72°W., 27.6' (1984)  
A 5/8" iron rod with YPC "HIBBS LS 52989" bears S.88°W., 204.2'  
A 5/8" iron rod with YPC "HIBBS LS 52989" bears N.68°E., 218.9'.

Note - Hibbs set corners during a survey that has not yet been recorded (Set chaining nail at side center, BT signs on front and rear, painted red band for existing BT'S, and set posts with BT signs at 5/8" iron rods)

Established the following:  
A Fir 16" dia., bears N.82°W., 92.3' mkd ¼ S8 BT.

Continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 10" dia., bears N.18°W., 101.8' MKD: ¼ Fir S8 BT  
(Set chaining nail at side center, nail and washer stamped  
"PLS 2830" at base of blaze, BT signs on front and back and  
painted red band for new BTs)

Fd BC by N Hibbs 5/2024 - M185-11