

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5772)

-----  
Set a post, cor. of secs. 4, 5, 8 and 9, from which  
A B.Oak 10" dia., bears S.33°E., 64 lks. dist.  
A B.Oak 7" dia., bears N.79°E., 65 lks. dist.  
A B.Oak 18" dia., bears S.78°W., 26 lks. dist.  
A W.Oak 8" dia., bears N.40°W., 762 lks. dist.

GL0 resurvey by Mensch, 1924 - (DCSO records, Vol. 14 Pages 5891-92)

-----  
Intersect the point for sec. cor. located by record measurement from the original bearing trees. Marks on all these trees are overgrown, blazes are plain. NE tree opened. At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd:

T28S	R7W
<u>S5</u>	<u>S4</u>
S8	S9
1924	

from which (Original bearing trees):

- A B.Oak 14" dia., bears N.79°E., 65 lks. dist.
- A B.Oak 18" dia., bears S.70°E., 64 lks. (Not S.33°E.)
- A B.Oak 30" dia., bears S.80°W., 26 lks. (Not S.78°W)
- A W.Oak 20" dia., bears N.38°W., 162 lks. (Not N.40°W., 762 lks.)

New BTs -An Ash 8" dia., bears N.77°E., 18 lks. dist. mkd.

T28S R7W S4 BT.

A Cedar 10" dia., bears S.77°E., 19 lks. dist., mkd.

T28S R7W S9 BT.

A Fir 16" dia., bears S.55°W., 34 lks. dist., mkd.

T28S R7W S8 BT.

A Cedar 10" dia., bears N.62°W., 23 lks. dist., mkd.

T28S R7W S5 BT.

Doug. County Surveyors Office - James W. Byron - Milo Godfrey and Clete Putnam - Feb. Mar. 1961 - C.S. File 49/50-36

-----  
Found - Brass cap at cor. & stump of 8" now 14" Ash, N.77°E., 11.9 ft., shows good scribing.

Now 16" Cedar, down, that shows good scar, N.62°W., 15.2 ft.

No other orig. or 1924 survey BTs found.

New BTs -6" W.Oak bears N.41°E., 27.3 ft. scribed S4 T28S R7W CS BT.

18" Cedar bears S.61½°W., 49.5 ft. scribed S8 T28S R7W CS BT. (Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor 4, 5, 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

5" W.Oak bears N.19°E., 23.5 ft. scribed S4 CS BT.  
No trees near to NW.  
18" R.Fir bears S.5½°E., 56.0 ft scribed S9 T28S R7W  
CS BT.

Doug. County Surveyors Office - L.E. Monrean, Deputy - P.L. Earle - Oct. 4, 1976 - C.S. File 59/24-22

-----  
Found - No trace of brass cap set in 1924.  
Did not find any orig. or 1924 resurvey BTs.  
Three BTs from 1961 renewal still standing, from  
which I set a brass cap after opening a W.Oak and  
finding scribing "T28S R7W S4 CS" on the upper  
blaze.

Set Brass cap at sec. cor. stamped:

"Douglas County Surveyor's Office"  
T 28 S R 7 W  
S 5 | S 4  
S 8 | S 9  
1976

from which

- A W.Oak 6" now 8" bears N.41°E., 27.3 ft. Tree double blazed and scribed "T28S R7W S4 CS" on upper blaze. The lower blaze is well healed.
- A W.Oak 5" now 7" bears N.19°E., 23.5 ft. Tree has well healed double blaze.
- An 18" R.Fir now 24" , S.2½°E., 56.0 ft. (Rec. S.5½°E.) Tree has well healed double blaze.
- An 18" Cedar now a windfall, bears S.61½°W., 49.5 ft. Tree laying with blaze down.
- New BT - A 7" I.Cedar bears N.65½°W., 26.1 ft. Tree double blazed and scribed "T28S R7W S5 CS BT".

BLM resurvey - by Bishop & Rogers, under Group #1124 - Survey, April 1983/Jan. 1984 (DCSO records, Vol. 46 Pages 17752-53)

-----  
The sec. cor., perpetuated & recorded by Byron, 1961, from a BT mkd. by Mensch, no longer in existence, and further perpetuated and recorded by L. Monrean in 1976, monumented with and I.P. 1¼" dia., projecting 10" above ground, with properly mkd. brass cap.

from which the remains of BTs mkd. by Byron:

- A W.Oak 6" dia., N.19°E., 36 lks. with a healed double blaze.
- A W.Oak 8" dia., N.41°E., 41 lks. with marks T28S R7W S4 CS visible on an opened blaze.

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 18" dia., S.5½°E., 86 lks. with a healed dbl blaze.  
and a bearing tree mkd. by Monrean:  
A Cedar 8" dia., bears N.65½°W., 40 lks. dist., with  
scribe marks T28S R7W S5 CS BT visible on partially  
healed blaze.  
and a new bearing tree:  
A Fir 8" dia. bears S.60½°W., 62 lks. dist., mkd.  
T28S R7W S8 BT.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, &  
Robert J. Chappel, Cadastral Surveyor, under Group #1585,  
surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s)  
20014-5)

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch  
& Crew - For: US Department of Interior, BLM - Petty Larsony  
- Task E -March 2023 - M185-3 A-D

-----  
Found - 2½" brass cap, 0.2' above ground from which:  
An Oak 8" dia., bears N.18°E. 23.4' w/BT sign (1961)  
An Oak 12" dia., bears N.40°E., 27.3' with healed  
blaze (1961)  
A Cedar 12" dia , bears N.62°W., 26.0' with healed  
blaze (1976)  
A 16" dia., Fir bears S.59°W., 40.5' w/healed blaze  
(1984)  
A 22" Fir 22" dia., S.7°E., 55.9' with healed blaze  
(1976)  
(Set chaining nail at side center, BT signs on front and  
rear, and painted red band for existing BTs)