

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5773)

-----  
Set quar. sec. post, from which  
A Laurel 8" dia., bears S.23°E., 60 lks. dist.  
A B.Oak 12" dia., bears N.35°W., 25 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5892-93)

-----  
Apportioned distance.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd:  $\frac{1}{4}$   
S5 S4  
1924

from which  
A Laurel 20" dia., N.70°E., 6 lks. dist. mkd.  $\frac{1}{4}$  S4 BT.  
A Laurel 14" dia., N.81°W., 33 lks. dist. mkd.  $\frac{1}{4}$  S5 BT.

Fd BC and witness trees. H. Northcraft, April/Nov. 1974 - M 54-55

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20015)