

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel For, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5220-21)

Set a post, cor. of secs. 4 and 5, from which
 A R.Fir 20" dia., bears S.35°E., 22 lks. dist.
 A Laurel 15" dia., bears S.30°W., 47 lks. dist.
For Standard Corner.

GL0 resurvey by Mensch, 1924 (DCSO records Vol. 14 Pages 5872-73)

Intersect the point for standard cor. of secs. 4 and 5, established by For, located by record bearing & distance from the orig. SW BT, blazes distinct, but marks weathered & decayed away. SE BT has rotted away.
At the exact cor. point
Set an Iron post, 3 ft. long, 2" dia., 28" in the ground, for standard NW. cor. of Sec. 4 only, with brass cap mkd.

S4
T28S
R7W
SC
1924

from which (new bearing trees)
 A Laurel 12" dia., bears S.72°E., 45 lks. dist. marked
 S C T28S R7W S4 BT.
 An Oak 4" dia., bears S.29°E., 12 lks. dist. marked
 S C T28S R7W S4 BT.
Orig. SW BT, a Laurel 20" dia., bears S.30°W., 47 lks.
Evidence of the SE BT, a Fir bears S.35°E., 22 lks.
New NE cor. of Sec. 5, bears S.4°52'E., 3.30 chs. dist.
The cor. established by Hathorn for standard cor. of secs. 4 & 5, restored as angle point No. 6 of resurveyed Sec. 33, bears S.35°34'W., 4.06 chs. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-35

At corner point, found Iron pipe with brass cap. (1924)
12" Laurel S.72°E., 29.7 ft. shows scar.
Oak BT, called for gone, no trace.
Laurel, S.30°W., 31 ft., still standing, but rotted out inside.
New BT - 10" Fir N.55°E., 6.3 ft. (NW S4 CS BT).

Found OK, James Artman, April 1990, M 110-5