

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 332700

PRIMARY CORNER DESCRIPTION Angle Point on N. Bdy Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, Under Contract #44 dated May 30, 1854 (DCSO records, Volume 12 Page 5220)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears N.53°W., 35 lks. dist.
A W.Oak 10" dia., bears N.70°E., 20 lks. dist.

GL0 survey by Fred Mensch, Contract #109 dated 1924 (DCSO records, Volume 14 Pages 5871-72)

Intersect the point established by Ford for the ¼ sec. cor. of sec. 33, located by measurement from the stumps of the original bearing trees, which are now badly decayed, but showing evidence of the old blazes.

At the exact cor. point, Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for Angle Point, with brass cap mkd.

AP
1924

from which (new bearing trees)
A Fir 8" dia., bears S.79°E., 48 lks. dist. mkd. AP BT.
A Fir 18" dia., bears S.56°W., 40 lks dist. mkd. AP BT.
The original NE bearing tree, a White Oak stump, bears N.70°E., 20 lks. dist.
Original NW. bearing tree, a Black Oak stump bears N.53°W., 35 lks. dist.
The cor. established by Hathorn for ¼ sec. cor. of sec. 33, restored as ¼ sec. cor. and angle point @10 of resurveyed 33, T.27-7 bears S.36°43'W., 2.26 chs. dist.

Doug. County Surveyors Office - James W. Byron, Deputy; Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-29

Found - Brass cap at corner mkd. AP 1924.
Stump of SW BT, good scribing.
SE BT not found.
New BTs- 8" Cedar bears N.76°W., 16.2 ft. scribed AP CS BT.
(scribed high above fence)
R.Fir bears S.8°W., 33.4 ft. scribed AP CS BT.

Fd. & used BLM resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO Records Vol. 50 Page(s) 19149-50)