TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5768-69)

Set quar. sec. post at average dist., from which
A W.Oak 36" dia.,bears S.16°E., 52 lks. dist.
A W.Oak 20" dia., bears N.30°E., 120 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - John M. Powell and crew - March 1969 - C.S. File 54/83; M 33-57

This corner set from survey at prorated distance.
Set Brass cap at cor. mkd: County Surveyor's Office 1969 T 28 S R 7 W ¼ S 28 / S 33
New BTs -14" Hemlock S.52°E., 24.0 ft. mkd. "¼ S33 CS BT".
13" S.Pine N.72°W., 51.1 ft. mkd. "¼S28 CS BT".

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Jan. 17, 2012 - C.S. File 67/36-3

Found - 1969 2½" dia., BC (properly mkd) on 1" I.D. IP, firmly set and protruding 14" above ground.
A wide search was made for the orig. BTs; no good evidence was found.
A 14" hemlock now a 27" DBH 6 ft. tall rotted hemlock stump with a previously healed double blaze, the upper blaze of which has been opened to show "¼ S33 CS" This stump bears S.54°E., 24.0 ft. (rec. S.52°E., 24.0 ft.) 1969
A 13" S.Pine now a low cut 30" dia., 1.0 ft. tall pine stump with the rotted remnants of a lower blaze with the scribing "BT" evident. This stump bears N.73½°W. 51.1 ft (Rec N.72°W. 51.1 ft) 1969
New - An 11" DBH D.Fir scribed "¼ S28 CS" "BT" on a double blaze; bears N.84½°E., 11.2 ft.
A 13" DBH D.Fir scribed "¼ S33 CS" "BT" on a double blaze; bears S.32°E., 48.1 ft.
A 6" DBH G.Fir scribed "X" "CS BT" on a high-low blaze; bears S.77¼°W., 24.4 ft.
A 13" DBH B.Oak scribed "¼ S28 CS" "BT" on a double blaze; bears N.11°W., 41.6 ft.
Note - Monument is on low partially forested plane and is about 250 ft. North from Tenmile Creek.
Compass decl. 15¾°E.

Found brass cap by Neil Hibbs 4/2014, M166-8