

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 16 and 21

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5771)

Set quar. sec. post at average dist., from which
A B.Oak 6" dia., bears N.30°W., 55 lks. dist.
A B.Oak 10" dia., bears S.45°E., 17 lks. dist.

Wm. C. Stiles, Seek Inc. For: L & H Lumber Co. - March 1967
C.S. File 55/32; M 32-76

Established by single prop. measurement, S.89°33'10"E.,
2627.52 ft. from corner to sections 16, 17, 20 and 21.
Set - 1½" galv. I.Pipe, from which
12" D.Fir, N.29°21'09"W., 13.0 ft. scribed ¼ S16
BT.
14" D.Fir, S.34°16'51"W., 13.5 ft. scribed ¼ S21 BT.

Glenn Baughman, L.S. #536 For: Glide Lumber Products - June
1984 - C.S File 58/114; RM 3-62

Found - 1" Iron pipe.
17" D.Fir N.29°W., 13.0 ft., healed blaze.
16" D.Fir S.34°W., 13.5 ft., healed blaze.
Set - 5/8" x 30" Iron rod mkd. "Baughman Tech. Serv."
BTs - 17" D.Fir, N.29¼°W., 5.6 ft.
16" D.Fir S.12½°W., 17.7 ft.
Set Iron pipe bears N.30°01'17"W., 7.24 ft. from found I.P.

BLM dependent resurvey by Bryan S. Seibold, & Robert J.
Chappel, Cadastral Surveyor, under Group #1585, surveyed May
1991/May 1994 - (DCSO records Vol. 52 Page(s) 20014)

The ¼ sec. cor. of secs. 16 & 21, reestablished by Baughman,
in 1984, and is accepted as the corner; monumented with an
iron rod, 5/8" diam., firmly set, projecting 6" above ground,
with plastic cap mkd. BAUGHMAN TECH SERV, from which bearing
trees mkd. by Stiles in 1967 and used by Baughman:

A fir, 17" diam., bears S.12¼°W., 26½ lks., with healed
blaze.

A fir, 18" diam., bears N.26½°W., 9 lks., with healed
blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 22" in the
ground, directly over the iron rod, with brass cap mkd.

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 16 and 21

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

T28S R7W
1/4 S16
S21
1992

From this point, a point established as the 1/4 sec. cor. of secs. 16 & 21 by Stiles, in 1967, bears S.30°21'30" E., 0.109 chs.; monumented with an iron pipe, 1 1/2" diam., firmly set, projecting 4" above ground.
This corner was rejected and was not used in this survey.