

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 9 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5772)

-----  
Set quar. sec. post at average dist., from which  
A W.Oak 15" dia., bears N.80°E., 125 lks.  
A W.Oak 30" dia., bears S.10°E., 37 lks.

BLM resurvey by James E. Jelley - under Group #878, Survey, July/Aug. 1975 (DCSO records, Vol. 37 Pages 15419-20)

-----  
Point for the 1/4 cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:  
1/4     S 9  
         S 16  
         T 28 S R 7 W  
                 1975

from which  
A Fir 17" dia., bears N.77½°E., 38 lks. mkd. ¼ S9 BT.  
A Fir 6" dia., bears S.36°E., 51 lks. mkd. ¼ S16 BT.

Fd. OK, BLM resurvey by Bishop & Rogers, April 1983/Jan. 1984 (DCSO records. Vol. 46 Pg. 17749)

Glenn Baughman, L.S. #536 0 For: Glide Lumber Products - June 1984 - C.S. File 58/114; RM 3-62

-----  
Found - 2½" I.P. with BLM brass cap.  
20" D.Fir N.64°E., 24.4 ft. (Rec. N.77½°E., 25.1 ft.)  
8" D.Fir S.36°E., 33.4 ft.  
Set - 5/8" x 30" Iron rod mkd. "Baughman Tech. Serv."  
20" D.Fir N.58°E., 20.1 ft., healed blaze.  
8" D.Fir S.30½°E., 32.1 ft., healed blaze.  
Set Iron pipe bears N.73°46'16"E., 4.52 ft. from found B.C.

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Petty Larsony - Task E - March 2023 - M185-3 A-D

-----  
Found - 3¼" brass cap (properly mkd) , 0.7' above ground from which:  
A 5/8" iron rod bears N.74°37'25"E., 4.48' (survey coordinates) continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir 24" dia., bears N.60°E., 24.5' with healed blaze and BT sign (1975)  
A stump 12" dia. (7' high), bears S.40°E., 33.6' with healed blaze (1975) (set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)  
Established the following -  
A Fir 10" dia., bears S.52°E., 21.7' mkd: ¼ S16 BT (Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BT)