TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Subd. of Section, by Bishop and Rogers, under Group #1124, survey April 1983/Jan. 1984 (DCSO records, Vol. 46 Pages 17756-57)

Point for the center 1/4 cor., at intersection with the E. and W. center line.
Set an Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 7 W
C 1/4
S 9
1983

from which
A Cedar 8" dia., bears N.8°E., 11 lks. mkd. C ¼ S9 BT.
A Fir 10" dia., bears S.12°E., 19 lks. mkd. C ¼ S9 BT.

Fd. BC & BTs 12/2022 - N. Hibbs - M178-61

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Petty Larsony - Task E -March 2023 - M185-3 A-D

Found - 3" brass cap (properly mkd), 0.5' above ground from which:
A Fir 16" dia., bears S.24°E., 12.7' with healed blaze and BT sign (1983)
A Cedar 12" dia., bears N.15°E., 7.4' with partially healed blaze (1983)
(Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)

Fd BC by N Hibbs 5/2024 - M185-11
Fd OK by N. Hibbs 8/2025 - M186-32