

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5772-73)

-----  
Set quar. sec. post at average dist., from which  
A B.Oak 5" dia., bears S.50°E., 33 lks. dist.  
A B.Oak 10" dia., bears N.40°E., 114 lks. dist.  
A house, bears S.45°W., 5.50 chs.

Doug. County Surveyors Office - G.G. Stewart - A.O. Strickland; A. Dysert; A. Erickson - March 16, 1922 - Vol. 3 Page 108

-----  
Renew from orig. BT standing. Set gun barrel for corner.  
Marked:  
Laurel 8" dia., bears N.54°E., 29.0 ft.  
Pine 12" dia., bears S.4°W., 56.0 ft.

GL0 resurvey by Mensch, 1924 - (DCSO records Vol. 14 Pages 5890-91)

-----  
Intersect the ¼ sec. cor., restored by Co. Surveyor, which is a 1" iron pipe, driven even with the surface ground. Alongside the iron pipe  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd: ¼  $\frac{S\ 4}{S\ 9}$   
1924

from which  
Orig. BT, a B.Oak 30" dia. bears N.49½°E., 114 lks. (not N.40°E.) blazes plain, marks grown over.  
New Bearing trees by County Surveyor  
A Pine 16" dia., bears S.4°W., 84 lks. dist. mkd. ¼ S CS BT.  
A Laurel 8" dia., bears N.53°E., 70 lks. dist., mkd. ¼ S CS BT.  
Could find no trace of the original SE Bearing tree.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - April 27, 1961 - C.S. File 49/50-52

-----  
Found - Old rifle barrel in fence corner - fences East and North.  
Old B.Oak, dead & burned out inside, N.49½°E., 75.2 ft. (This checks one orig. BT.)  
Stump hole, S.4°W., 55.4 ft. (This checks location for one of Mensch's trees.)  
No brass cap found at cor. and no trace of other BTs.  
(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Located directly under power line right of way, for which has been slashed & burned several years ago.

Alongside rifle barrel, set Iron pipe with brass cap marked:  
County Surveyor's Office, 1961  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{4}{9}$  T28S R7W

Blaze and scribe two new BTs:

11" D.Fir N.18°W., 33.1 ft. mkd:  $\frac{1}{4}$  S4 CS BT.

9" Pine S.9°W., 22.5 ft. mkd:  $\frac{1}{4}$  S9 CS BT.

BLM resurvey by Bishop and Rogers, under Group #1124. Survey, April 1983/Jan. 1984 (DCSO records, Vol. 46 Page 17754)

-----  
The  $\frac{1}{4}$  sec. cor., perpetuated and recorded by G.G. Stewart, 1922, from orig. evidence no longer in existence, and further perpetuated & recorded by Byron, 1961 with brass cap.

from which the remains of bearing trees by Byron:

A Pine stump, 9" dia., bears S.9°W., 34 lks. dist.,  
with marks S9 CS BT visible on an opened blaze.

A rotted Fir stump 15" dia., bears N.18°W., 51 lks. dist.,  
no marks visible.

and new bearing trees:

A Fir 8" dia., bears S.59 $\frac{1}{4}$ °E., 38 lks., mkd. 1/4 S9 BT.

A Fir 13" dia., bears N.28 $\frac{1}{2}$ °W., 95 $\frac{1}{2}$  lks., mkd. 1/4 S4 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/28/1998 - C.S. File 66/2-18

-----  
Found - 2 $\frac{1}{2}$ " dia., brass cap on a 1 $\frac{1}{2}$ " O.D. iron pipe, protrudes 14" above ground, properly marked. 1961 Gun barrel flush with ground is found N.45°E., 0.3' from BC/IP. 1922

11" now 15" dia., badly rotted D.Fir stump, illegible scribing found, bears N.18°W., 33.7'. (Agrees w/rec.) 1961

8" now 13" dia., D.Fir, with a fully healed double blaze, bears S.59 $\frac{1}{4}$ °E., 25.1'. (Agrees w/rec.) 1983

13" now 17" dia., dead D.Fir, w/fully healed double blaze, bears N.28 $\frac{1}{2}$ °W., 63.0' (Agrees w/rec) 1983

No other BTs found.

New BTs- 9" dia., D.Fir, double blazed and scribed " $\frac{1}{4}$  S4 CS BT" bears N.33 $\frac{1}{2}$ °W., 47.2'.

15" dia., Madrone, double blazed and scribed " $\frac{1}{4}$  S9 CS BT" bears S.33 $\frac{1}{2}$ °E., 27.0'.

8" dia., I.Cedar, double blazed and scribed " $\frac{1}{4}$  S4 CS BT" bears N.6°E., 49.6'.

Fd. BC by N. Hibbs, 10/2009 - M160-21

Fd. BC by G Lang, 7/2019 - M175-77