

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 373700

PRIMARY CORNER DESCRIPTION Angle Point N. Bdy. S. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathathiel Ford, Contract #44 dated May 30, 1854 (DCSO records, Volume 12 Page 5220)

Set a post, cor. of secs. 33 and 34, from which
 A Laurel 12" dia., bears N.65°W., 25 lks. dist.
 A Laurel 15" dia., bears N.83°E., 87 lks. dist.

GL0 survey by Fred Mensch, Contract #109 dated 1924 (DCSO records, Volume 14 Page 5870)

Intersect the point for the cor. of secs. 33 and 34, established by Ford and located by record bearing and distance from the stump of the original NW. bearing tree. The marks are obliterated by decay, but evidence of the blazes are still distinguishable. No evidence of the NE. BT is found.

At the exact point, Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for Angle Point, with brass cap mkd: AP
1924

from which (new bearing trees)
 A Fir 9" dia., bears S.66°E., 30 lks. dist., mkd. AP BT.
 A Fir 14" dia., bears S.85°W., 9 lks. dist., mkd. AP BT.
Stump of original NW. bearing tree, a Laurel, 18" dia., bears N.65°W., 25 lks.
The cor. established by Hathorn for the cor. of secs. 33 and 34, bears S.32°W., 1.37 chs. dist.

Doug. County Surveyors Office - James W. Byron, Deputy; Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-23

Renew Angle Point which bears N.32°E., 90.4 ft. from Sec. Cor. for 33 and 34 only.
Found - Brass cap at corner.
New BTs - 12" Laurel bears S.71°E., 63.0 ft. scribed AP CS BT
 12" W.Fir bears N.29°W., 41.3 ft. scribed AP CS BT.