

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. 33 & 34; 3 & 4 of T29-7

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5748-49)

-----  
Set a post at cor. of secs. 3, 4, 33 and 34, from which  
A W.Oak 24" dia., bears S.80°E., 235 lks.  
A B.Oak 8" dia., bears N.75°E., 236 lks.  
Impracticable to make a mound.  
No timber in a reasonable distance.

Arthur Boyer, for: A. Gilbert - Oct. 1958 - M 12-72

-----  
From Orig. BT, S.80°E., 235 lks., which Eugene Ollivant testifies is orig. BT. This tree has deep cut on NW face & old axe marks in cut & is East 2647 ft. from N ¼ cor. Sec. 4. Drove 2" sq. head bolt & remarked orig. BT.  
Scribed new trees:  
24" Cedar S.27½°E., 44.5 ft. "S3 T29S R7W 1581 BT".  
14" forked W.Oak N.34°E., 181.0 ft. "S34 T28S R7W".  
7" W.Oak S.89°W., 61.0 ft. "S4 T29S R7W 1581 BT".  
Corner is about 300 ft. West of center Olalla Creek and N. side of Dry Creek.

Glenn Baughman, LS #536, for: Douglas Co. Lumber - August 1980 - M 85-35; C.S. File 58/144

-----  
Found - Orig. 30" Oak with deep axe marks, bears S.80°E., 155.1 ft.  
24" now 36" Cedar with healed face bears S.27½°E., 44.5 ft.  
7" now 10" Oak with healed face bears S.89°W., 61.0 ft.  
14" now 30" double Oak stump with healed face bears N.34°E., 181.0 ft.  
Set - 5/8" x 30" Iron rod from bearing trees.  
Placed BT tags on all trees.