

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5762-63)

Set a post, cor. of secs. 27, 28, 33 and 34, from which
A W.Oak 36" dia., bears N.85°E., 550 lks. dist.
A W.Oak 30" dia., bears S.86°E., 580 lks. dist.
A W.Oak 20" dia., bears S.25°W., 334 lks. dist.
Made a mound, there being no tree within a reasonable distance.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - April, 1961 - C.S. File 49/50-50

Found - Orig. 20" now 34" W.Oak S.25°W., 220.4 ft. This BT was opened years ago, 50 years. We open & find old axe work but center rotted. No scribing found.

No other orig. BTs found.

We also find old Oak stake at corner & in place. I believe that BT was opened and stake set by Thiel, 1899, see cemetery survey. (file #??)

We rerun Thiel's tie to NW corner of cemetery and fall about one chain North but OK East and West tie from sec. cor. to SE corner DLC 51 checks OK.

Set B. cap at cor. alongside Oak stake, mkd. S28|S27 T28SR7W
County Surveyors Office, 1961 S33|S34

BTs - 30" W.Oak, N.29½°W., 178.0 ft. scribed S28 T28S R7W CS BT.

17" W.Oak bears N.69°E., 98.9 ft. scribed S27 T28S R7W CS BT.

10" W.Oak bears S.65°E., 270.0 ft. scribed S34 CS BT.

Rescribe orig. now 34" W.Oak S.25°W., 220.4 ft. "S33 T28S R7W CS BT".

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20005)