

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 15 & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5765)

Set quar. sec. post, from which
A B.Oak 6" dia., bears N.25°E., 18 lks.
A Laurel 12" dia., bears N.15°W., 32 lks.

Bureau of Land Management resurvey by James E. Jelley under Group #878, Survey, July/Aug. 1975 (DCSO records, Vol. 37 Page 15416)

Point for the ¼ cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:
1/4
S 16 S 15
T 28 S R 7 W
1975

from which
A Fir 5" dia., bears S.70 3/4°E., 85 lks. dist. mkd.
1/4 S15 BT.
A Myrtle 4" dia., bears N.17 3/4°W., 72 lks. dist. mkd.
1/4 S16 BT.

Glenn Baughman, L.S. #536, for: Glide Lumber Products - June, 1984 - C.S. File 58/144; RM 3-62

Found - 2½" I.P. with BLM brass cap.
6" W.Fir, S.71°E., 56.1 ft. (scribe visible)
14" Myrtle N.17°W., 47.7 ft. (scribe visible)
Set 5/8" x 30" Iron rod mkd. "Baughman Tech. Serv."
BTs - 6" W.Fir S.73½°E., 54.6 ft.
14" Myrtle S.16 3/4°W., 51.3 ft.
Set Iron pipe bears S.3°58'32"E., 3.64 ft. from found brass cap.

Howard Johnstone, For: Roseburg Resources - November, 1988
M 101-45

Found - BTs and 1975 Cadastral brass cap/iron pipe.
Reset monument at Baughman location from BTs.
Set - 5/8" x 36" Iron rod and alum. cap mkd. 1/4 16, 15.
BTs - 6" Fir S.71°E., 56.1 ft. scribe visible.
14" Myrtle N.17°W., 47.7 ft. scribe visible.
Cadastral BCIP bears N.4°W., 3.64 ft.