

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5766-67)

-----  
Set quar. sec. post, from which  
A B.Oak 6" dia., bears S.40°E., 21 lks. dist.  
A B.Oak 12" dia., bears N.80°W., 22 lks. dist.

G.G. Stewart, Deputy Co. Surveyor - A.O. Strickland; A. Dysert; A. Erickson - March 16, 1922 - Vol. 3 Pg. 108

-----  
Renew from old BT, one standing and one down.  
Set Iron pipe. Marked:  
Fir 10" dia., bears N.51°E., 22.0 ft.  
B.Oak 18" dia., bears N.80°W., 14.5 ft. (O.B.T.)

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - March 1961 - C.S. File 49/50-37

-----  
Found - Both BTs & ½" I.P. at corner. All as recorded by Stewart, 1922. The B.Oak to NW., now snag, shows good scribing "BT". Fir to NE., now stump.  
Set Brass cap at cor. mkd: County Surveyor's Office, 1961  
¼ S9|S10 T28S R7W  
New BTs -8" R.Fir bears S.68°E., 31.9 ft. scribed ¼ S10 CSBT.  
15" R.Fir bears N.19°W., 5.7 ft. scribed ¼ S9 CS BT.

Bureau of Land Management resurvey by Bishop & Rogers, under Group #1124, Survey April, 1983-Jan. 1984 (DCSO records, Vol. 46 Pages 17747-48)

-----  
Cor. perpetuated & recorded by Stewart, 1922, from original evidence no longer in existence, & further perpetuated & recorded by Byron, 1961, monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with properly mkd. brass cap  
from which the remains of bearing trees mkd. by Byron  
A Fir 14" dia., bears S.68°E., 49 lks. dist. with a healed blaze.  
A Fir stump 17" dia., bears N.20°W., 8 lks. dist. with a healed blaze.  
and a new bearing tree  
A Fir 17" dia., bears S.56 ¾°W., 23 lks. dist., mkd. 1/4 S9 BT.

Fd. Ok - Maurice E. Farr - March 31, 1993 - M118-67

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Petty Larsony - Task E -March 2023 - M185-3 A-D

Found - 2½" brass cap (properly mkd), 1.2' above ground from which:

A roothole bears N.72°E., 18' with 22" dia., Oak trunk alongside and BT sign from 2002 (no record)

A fir 24" dia., bears S.62°W., 14.8' with healed blaze and BT sign (1983)

A Fir stump 16" dia. (7' high), bears N.14°W., 5.5' with partially healed blaze (1961)

A Fir stump 14" dia., rotted, bears S.72°E., 32.0' (1983) (Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)

Established the following -

A Fir 12" dia., bears N.22°E., 22.1' mkd: ¼ S10 BT (Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BT)