

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Standard Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5220)

Set a post, cor. secs. 3 and 4, from which
 A B.Oak 10" dia., bears S.35°E., 9 lks. dist.
 A B.Oak 6" dia., bears S.12°W., 30 lks. dist.
For Standard Corner.

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5230)

Set post, cor. of secs. 3 and 4, from which
 A Laurel 24" dia., bears S.32°E., 42 lks. dist.
 An Oak 24" dia., bears S.56°W., 55 lks. dist.

Briggs: June 28, 1893 - Vol. 1 Page 252 and Field Book 106 Pages 36-38

Set post, marked.
Old Wit trees badly decayed. Marked N.W.T.
 Fir 8", S.57°E., 13 lks.
 Fir 6" S.12°W., 7 lks.

GL0 resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5869-70)

Intersect the point for standard cor. of secs. 3 and 4, established by Ford, located by record bearing and measurement from the original SE BT, and evidence of the orig. SW BT.

At the exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. the ground, with brass cap mkd:

S4:S3
T28S:R7W
SC
1924

from which (new bearing tree)
 A Fir 24" dia., bears S.56°E., 13 lks. dist. mkd. S C
 T28S R7W S3 BT.

 A Fir 14" dia., bears S.13°W., 8 lks. dist., mkd. S C
 T28S R7W S4 BT.

Original SE BT, now a rotted & decayed B.Oak stump bears S.35°E., 9 lks. dist.

Depression in the ground, evidently the position of the SW BT, bears S.12°W., 30 lks. dist.

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Standard Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corn. point further evidenced by old decayed stake (oak), marks still legible, set by local surveyor. The corner established by Hathorn for standard cor. of secs. 3 & 4, restored as angle point, bears S.34°53'W., 113 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-24

Found - Brass cap at corner and SW BT.
New BTs- 17" R.Fir bears S.36°W., 36.8 ft. scribed S4 T28S R7W CS BT.
15" R.Fir bears South 51.0 ft. scribed S3 T28S R7W CS BT.

Found OK, James Artman, April 1990, M 110-5