

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5763)

Set quar sec. post at average dist., from which
A B.Oak 12" dia., bears N.35°W., 20 lks. dist.
A B.Oak 20" dia., bears S.41°W., 67 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - V.R. Tracy; J. Heritage; V. Perron - March 1969 - C.S. File 54/83; M 33-57

Found - Orig. 12" now 28" B.Oak N.35°W., 13.2 ft. opened and found good scribing of "BT"
Orig. 20" now 30" B.Oak windfall and out of place, but has a good stump hole, S.41°W., 44.2 ft. shows very little in way of a face.

Set Brass cap at cor. mkd: County Surveyor's T 28 S R 7 W
Office 1/4 S 27
1969 S 34

New BTs -11" Madrone N.88°E., 15.4 ft. mkd. "1/4 S27 CS BT".
8" W.Oak S.55°W., 22.1 ft. mkd. "1/4 S34 CS BT".

This corner lies on a steep, west slope.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20004-5)