

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 15 and 22

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

| | | | | |
|---|------|------|-----|------|
| <p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5765)</p> <p>-----</p> <p>Set quar. sec. post at average dist., from which A B.Oak 10" dia., bears N.33°W., 125 lks. dist. A B.Oak 18" dia., bears S.27°E., 138 lks. dist.</p> | | | | |
| <p>G. R. Lecklider, for: C.M. McDermott - March 1959 - M 14-18</p> <p>-----</p> <p>Set 1/2" Rod in mound of stone, from which 11" Fir S.79°W., 28.9 ft. 11" Fir N.06°W., 14.0 ft. Original corner not found.</p> | | | | |
| <p>Bureau of Land Management resurvey by James E. Jelley, under Group #878. Survey, July/Aug. 1975 (DCSO records, Vol. 37 Page 15414)</p> <p>-----</p> <p>Point for ¼ cor., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd;</p> <table border="0"><tr><td></td><td>S 15</td></tr><tr><td>1/4</td><td>S 22</td></tr></table> <p>T 28 S R 7 W 1975</p> <p>from which A Fir 15" dia., bears N.33 3/4°E., 59 lks. dist., mkd. 1/4 S15 BT. A Cedar 16" dia., bears S.27 3/4°W., 96 lks. dist., mkd. 1/4 S22 BT.</p> <p>From this point, a local corner established by G.R. Lecklider, Registered Logging Engineer #4079, in 1959, bears N.19°00'E., 0.092 chs. dist., monumented with a rebar, 1/2" dia., firmly set, projecting 6" above ground, from which bearing trees by Lecklider: A Fir 15" dia., bears N.6½°W., 22 lks. with healed blaze. A Fir 15" dia., bears S.79½°W., 42½ lks. with healed blaze.</p> | | S 15 | 1/4 | S 22 |
| | S 15 | | | |
| 1/4 | S 22 | | | |
| <p>Bruce Shaner - June 30. 1997 - C.S. 65/15-3E & M 124-56</p> <p>-----</p> <p>Mon. Fd.- 3¼" Brass cap on 2½" Iron pipe Bt's Fd.- 20" Fir BT, face o/g, bears N.33 3/4°E., 38.9' 22" Cedar BT, face o/g, bears S.72 3/4°W., 63.4' (record S.27 3/4°W) ½" Rebar (steel) set by Leckleider for corner, bears N.19°E., 6.4'. (Cont. Next Page)</p> | | | | |

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 15 and 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New Accessories -

I tied Leckleiders BT's to USBLM Corner:

22" D.Fir BT, face overgrown, bears N.4°E., 20.3'

22" D.Fir BT, face overgrown, bears N.86°W., 26'.

Corner is On a E-W Timber Edge