

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5766)

Set quar. sec. post at average dist., from which
A B.Oak 15" dia., bears S.10°W., 18 lks. dist.
A Laurel 18" dia., bears N.5°E., 30 lks. dist.

Doug. County Surveyors Office - J.W. Byron; V. Tracy & crew
April 8, 1969 - C.S. File 54/85

Prorated ¼ corner and Set brass cap between section corners.
Set Brass cap at cor. mkd: County Surveyor's T 28 S R 7 W
Office, 1969 ¼ S 10
S 15

New BTs -9" B.Oak N.4°W., 8.4 ft. mkd. "¼ S10 CS BT"
11" W.Oak S.44°E., 5.8 ft. mkd. "¼ S15 CS BT".
Find no trace of orig. BTs. Corner lies on steep easterly
slope of ridge.

BLM resurvey by James Jelley, 1975, found brass cap and BTs.
(DCSO records, Vol. 37 Page 15418)

Fd. Ok - March 31, 1993 - Maurice E. Farr - M118-67
Fd. Ok by Neil Hibbs, 8/2007 - 2007-0105 A & B