

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5767)

Set quar. sec. post at average dist., from which
A W.Oak 12" dia., bears N.85°E., 125 lks. dist.
A W.Oak 10" dia., bears S.85°W., 120 lks.

G.G. Stewart, Deputy Co. Surv. - A.O. Strickland; A. Dysert; A. Erickson - March 16, 1922 - Vol. 3 Page 108

Renew from stump of old BT., has letters "BT" scribed on it.
Set sq. Cedar post. Marked:
W.Oak 8" dia., bears N.83½°W., 48.5 ft.
B.Oak 18" dia., bears South, 35.4 ft.

Doug. County Surveyors Office - Vernon Tracy, Deputy - Jack Heritage; Vince Perron - Sept. 1968 - C.S. File 52/79-32

Found - Orig. BTs, as recorded by Stewart, 1922:
8" now 22" W.Oak, alive, N.83½°W., 48.5 ft., shows scar, open above scar.
18" now 22" B.Oak, decayed stump, 6 ft. high, south 35.4 ft., find frag. scribe & reverse on blaze nearly surrounded by new trees.
Set Brass cap at cor. mkd: County Surveyor's T 28 S R 7 W
Office ¼ S 3
1968 S 10
Set 3/4" x 7 ft. I.P. alongside brass cap for marker.
New BTs- 7" W.Oak S.71°W., 31.2 ft. mkd. "¼ S10 CS BT"
22" W.Oak N.83½°W., 48.5 ft. mkd. "¼ S3 CS BT" above hole. (This is Stewart's BT.)
Corner lies in field 30 ft. N. of old fence line, SE-NW, following dry creek.
Also mkd: 36" B.Oak South 37.2 ft. mkd. "¼ S10 CS BT" (New tree surrounding remains of Stewart BT)

Fd. Ok - March 31, 1994 - Maurice E. Farr - M118-67

Fd. OK, Aug. 1995 by D.Bentz - M122-54
FD. OK, Mar. 1997 by D.Bentz - M 127-6
Fd. OK by D. Edwards, Dec. 1999 - M134-11
Fd. OK, Aug. 2002, by D. Edwards - M140-61