

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5756)

Set quar. sec. post, from which
A W.Oak 10" dia., bears N.10°E., 210 lks. dist.
A B.Oak 12" dia., bears N.5°W., 200 lks. dist.

F.J. Cole - Survey for R.F. Huntley - Crew: Earl Ollivant; Eugene Ollivant - Dec. 13, 1915 - Field Book 37 Pg. 1

Check and find trees:
B.Oak N.05°W., 201 lks. Marks visible.
B.Oak stump N.10°E., 200 lks., badly decayed inside. A scar shows on inside indicating old blemish.
Renew corner with post marked "1/4 S. C.S."

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov. 1958 - C.S. File 49/50-10

Found - Now 24" shell of 24" Oak stump N.10°E., 130.0 ft.
record 10" W.Oak N.10°E., 138.6 ft.
Orig. 12" now 44" B.Oak N.5°W., 132.0 ft. shows old scar, center rotted. I do not open.
6" x 4" x 24" Cedar stake on ground, 10 ft. West of corner scribed 1/4 S CS.
Set Brass cap at cor. mkd: 1/4 S34 | S35 T28S R7W County Surveyor Office, 1958.
New BTs -9" B.Oak bears N.74°E., 41.4 ft. scribed 1/4 S35 CSBT
18" W.Oak bears N.80°W., 6.5 ft. scribed 1/4 S34 CSBT.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20051)

The 1/4 sec. cor. of secs. 34 & 35, perpetuated by Cole, Deputy County Surveyor, in 1915, further perpetuated by Byron, Deputy County Surveyor, in 1958,; monumented with an iron post, 1 1/2" diam., firmly set, projecting 10" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T28S R7W
1/4 S34 | S35
1958

from which the remains of the original bearing trees
An oak stump, size indeterminate, bears N.7 1/2°E., 196 lks., no marks visible. (Record, N.10°E., 210 lks.)
continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The most westerly trunk of a double trunk oak, 29" diam., bears N.7°W., 248 lks., with partially healed, opened blaze. (Record, N.5°W., 200 lks. dist.)
and bearing trees mkd. by Byron
An oak, 17" diam., bears N.73¼°E., 63 lks., with healed double blaze.
An oak, 27" diam., bears N.81°W., 9½ lks., with healed double blaze.

Fd. Ok by Neil Hibbs, May 2003 - M 137-63
Fd. Ok by Neil Hibbs, Feb. 2009 - 2009-0019

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-23 A-C

Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1958
18" Oak with healed face N.73¼°E., 41.6'
30½" W.Oak with healed face N.81°W., 6.3'