

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec Cor for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5756-57)

Set a post, cor. of secs. 26, 27, 34 and 35, from which
A B.Oak 15" dia., bears N.85°E., 335 lks. dist.
A B.Oak 12" dia., bears S.82°E., 325 lks. dist.
No other trees within a reasonable dist.
Therefore, made a trench as per instructions.

J.W. Cole, Surveyor - Wit: R.K. Paris; L. Stevens - April 9, 1924 - Field Book 31 Page 22

I renewed this corner from the original bearing trees, both of which had been chopped open. Tree SE bore scribe marks. I set a 4 x 4 x 40" Cedar post, 5 ft. East of small creek and marked:
An Ash 8" dia., bears N.10°30'W., 5.9 ft.
A B.Oak 8" dia., bears S.63°30'W., 18.0 ft.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov. 1958 - C.S. File 49/50-9

Found - Scribed stake at corner and BTs as recorded by Cole. Scribing visible on now 12" Ash, N.10½°W., 5.9 ft. The SW BT shows good scar.
Set Brass cap alongside corner stake mkd: S27|S26 T28S R7W
County Surveyor's Office 1958 S34|S35
New BTs -9" R.Fir bears S.70°E., 28.8 ft. scribed S35 T28S R7W CS BT.
8" W.Oak bears N.27°E., 15.2 ft. scribed S26 T28S R7W CS BT.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20003)

Fd. BC & BTs by N Hibbs, 4/2017 - M171-26A&B