

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5757)

Set quar. sec. post, from which
A W.Oak 24" dia., bears N.35°E., 105 lks. dist.
A Maple 8" dia., bears S.55°W., 82 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - S.A. Bilow; Milo Godfrey - Nov. 1958 - C.S. File 49/50-6

Found - Orig. 24" now 36" W.Oak. I open & find good scribed "¼ S BT", N.35°E., 69.3 ft.
No trace of original SW BT.

Set Brass cap at cor. mkd. ¼ S27 | S26 T28S R7W County Surveyor Office, 1958

New BTs -22" R.Fir bears N.47°W., 27.5 ft. scribed ¼ S27 CSBT
10" W.Oak bears N.82°E., 34.3 ft. scribed ¼ S26 CSBT
Sketch in C.S. file for exact location of corner.

Fd. OK by C. Sweeden, April 1999 - M131-42

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20003-4)

The 1/4 sec. cor. of secs. 26 & 27, perpetuated by Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1½" diam., firmly set, projecting 8" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE

¼ S | S
27 | 26
T28S R7W
1958

from which the remains of an original bearing tree
A roothole, bears N.35°E., 105 lks., with uprooted oak, 39" diam., lying alongside, no marks visible on opened blaze.

and a remaining bearing tree mkd. by Byron
A fir, 34" diam., bears N.44½°W., 41½ lks., with healed double blaze.

and a new bearing tree
An oak, 8" diam., bears N.32 ¾°E., 23½ lks., mkd. ¼ S26 BT.