

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec Cor for 22, 23 26, 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5757-58)

Set a post, cor. of secs. 22, 23, 26, and 27, from which
A W.Oak 18" dia., bears S.23°E., 95 lks. dist.
A B.Oak 18" dia., bears S.44°W., 160 lks. dist.
A B.Oak 10" dia., bears N.33°W., 102 lks. dist.
A B.Oak 30" dia., bears N.65°E., 104 lks. dist.

(This cor. mentioned in C.S. File 5/25 pages 7 & 8 of notes)
No other record source found.

Renew from old BT. Set in a 1" x 1" x 24" Iron bar. Remark all old BTs except in section 23. This tree rotted.

Doug. County Surveyors Office - James Byron, Deputy - S.A. Bilow; Milo Godfrey - Nov. 1958 - C.S. File 49/50-8

Found - 1" x 1" Bar at corner and at fence corner.
Orig. 10" now 31" Oak stump shows reverse scribing "BT", N.33°W., 67.3 ft., if find 63.3 ft.
Orig. 18" now 32" W.Oak partly rotted, shows old scars, S.23°E., 62.7 ft.
Orig. NE and SW BTs gone.
I do not set brass cap at corner. Bar set by Frear, 1917 is OK.
New BTs -9" W.Oak bears S.23°W., 33.4 ft. scribed S27 T28S R7W CS BT.
15" Laurel bears N.31°W., 19.4 ft. scribed S22 T28S R7W CS BT.
6" R.Fir bears S.73°E., 22.7 ft. scribed S26 T28S R7W CS BT.
7" R.Fir bears N.70°E., 40.1 ft. scribed S23 T28S R7W CS BT.

Doug. County Surveyors Office - Vernon R. Tracy & crew. Feb. 3, 1969 - C.S. File 52/79-29

Found - 1" x 1" iron bar, 14" long, 8" above surface of ground.
9" now 10" W.Oak S.23°W., 33.4 ft. healed blaze.
15" now 16" Laurel N.31°W., 19.4 ft. scribe marks visible.
6" now 8" D.Fir S.73°E., 22.7 ft. healed blaze.
NE BT, now sawed stump, scribe visible.
(Cont. Next Page)

