

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5759)

Set a post, cor. of secs. 14, 15, 22 and 23, from which
A B.Oak 10" dia., bears S.43°E., 50 lks.
A B.Oak 8" dia., bears S.25°W., 38 lks.
A W.Oak 20" dia., bears N.63°W., 200 lks.
A W.Oak 6" dia., bears N.27°E., 331 lks.

Frear and/or Eppstein - June 1917 - Field Book 44 Page 17

Found - B.Oak 10", S.43°E., 50 lks., my measurements are S.39½°E., 50 lks., tree marked.
B.Oak 8", S.25°W., 38 lks. my measurements, same.
W.Oak 20", N.63°W., 200 lks., my measurements, N.61°W., 200 lks. Tree rotted, no marks.
W.Oak 6", N.27°E., 331 lks., my measurements are N.13°E., 333 lks., marked but nearly gone.
I then set a 14" x 6" x 8" boulder, from which I marked:
A 8" Fir N.28°50'E., 24.6 ft. "C.S.C. S14."
A 28" Fir N.37°30'W., 21.4 ft. "C.S.C. S15."
(F.C. Frear, in August 8, 1935, drove a 1" x 24" Ford axle North, 25.0 ft. and remarked the two old trees. ((Record Source for this info. ?))

Doug. County Surveyors Office - John Powell; J. Heritage
Dec. 22, 1971 - C.S. File 54/113-20

Found - 8" D.Fir now 26", N.28½°E., 24.6 ft. shows good scar.
28" D.Fir now 38", N.37½°W., 21.4 ft. barks scribe visible. Part of "BT" (to be cut)
Also found Ford axle, 25.0 ft. North of sec. cor.
Axle 2" x 14" not 1" x 24" as recorded.
Stone, 14" x 6" x 8", 3.0 ft. under surface of road (no marks) at sec. cor.
Set Brass cap along side axle mkd. County Surveyors T28S R7W Office W.C. 25' south to
1971 15|14
22|23
Also set 1¼" x 26" Iron rod over stone at sec. cor. This iron rod is in center of county road, 5" below surface.
New BTs -12" D.Fir S.61°E., 73.6 ft. scribed W.C. T28S R7W S23 CS BT.
16" D.Fir N.64°W., 108.6 ft. scribed W.C. T28S R7W S15 CS BT.
Brass cap lies 6.0 ft. North of fence along road.
(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. 14, 15, 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found OK, V.R.T., DCSO - July 1973, C.S. File 56/34-18
Brass cap & 4 BTs, found, BLM dependent resurvey by Jelley, 1975 (DCSO records, Vol. 37 Page 15412-13)
Corner referenced out May 9, 1977, for realignment and construction of Co. Rd. #108 - C.S. File 59/30
Doug. County Surveyors Office - Greg Quibell, Deputy - Karen Mosley; April 9, 1981 - C.S. File 61/19-65 ----- Found - I.P. with 1971 County brass cap W.C. properly mkd., firmly set flush with ground. 1¼" x 26" I.Rod lying buried at approx. corner location. 12" now 14" D.Fir bears S.61°E., 73.6 ft. from wit. cor. Partially healed, well pitched over, single blaze with an "8" visible. 16" now 20" D.Fir bears N.64°W. 108.6 ft. from Wit. Cor. Well healed single blaze. Both 5/8" Iron rods set North of cor. for reference. 8" now 33" D.Fir bears N.28½°E., 25.1 ft. to center. Did not find either 5/8" Iron rods set N.70°30'E., for reference. Set - Using the two 5/8" Iron rods set North of the cor. for reference, I RESET the 1¼" x 26" Iron rod. While digging the hole, I find what I assume to be the stone set by Frear, since this stone fits both the Wit. Cor. and the two reference 5/8" I.R.'s, I DRIVE the 1¼" x 26" I.R. alongside stone until flush with ground and end is directly over stone. I tied two C/L points to cor. for additional reference: From 1¼" I.R., PK nail, Sta. 146+00, 27.03 ft. From 1¼" I.R., PK nail, Sta. 146+21.27, 19.69 ft. Sec. Cor. now lies in a gravel pull off 7.5 ft. Northerly of North edge of pavement. Stone is approx. 16" in the ground.
Found OK by Bentz, Sept. 1996 - Partition Plat 1996-0081 Fd. Ok by Neil Hibbs, 8/2007 - 2007-0105 A & B Fd. 1¼": dia., iron rod, 10/2013 - M165-72 by D. Edwards
Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 8/15/25 - C.S. File 67/61-14 ----- Found - 2½" D.C.S.O. brass cap 4" below ground 1" axle shaft 1¼" iron rod stone approx 16" down - not looked for. 28" D.Fir S.80½°E. 65.3ft from corner (S.61°E. 75.5 rec to WC)
continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor 14, 15, 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

28" D. Fir S. $80\frac{1}{2}^{\circ}$ E. 65.3 ft from corner (S. 61° E. 75.5
rec to WC) fully healed single blaze. Add $3\frac{1}{2}$ " mag
nail right side center.
From iron rod - PK nail sta 146 + 00 27.03 ft mag signal.
PK nail 146+21.27 19.69 ft mag signal.
COUNTY SURVEYORS OFFICE
WC 25' SOUTH
TO
15|14
22|23
1971
See 1977 reference drawing, page 5 of 5 of this
file (C.S. 67/61-14)
Notes - Cor in gravel pull off 7.5 ft northerly of north
edge of pavement.
Compass decl. $14\frac{1}{4}^{\circ}$ E.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
 $43^{\circ}07'38.79836$ N.
 $123^{\circ}30'12.48941$ W.