

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5757)

Set quar. sec. post, from which
A W.Oak 24" dia., bears N.35°E., 105 lks. dist.
A Maple 8" dia., bears S.55°W., 82 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - John Powell and crew - March 1969 - C.S. File 54/83 and M 33-57

At proportional point on Section line between secs 26 & 35
Set Brass cap at cor. mkd: County Surveyor's T 28 S R 7 W
Office 1/4 S 26
1969 S 35

New BTs -10" D.Fir S.9°W., 47.3 ft. mkd. "1/4 S35 CS BT"
10" Laurel N.23°E., 6.5 ft. mkd. "1/4 S26 CS BT"
There is no evidence of original BTs. Fence corner bears N.50°E., 12.0 ft., fences N-S-E and W.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20049-50)