TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5758)

Set quar. sec. post at average dist., from which
A W.Oak 6" dia., bears S.60°E., 30 lks.
A W.Oak 13" dia., bears N.65°W., 18 lks.

Doug. County Surveyors Office - James W. Byron, Deputy M. Godfrey; S.A. Bilow - Nov. 1958 - C.S. File 49/50-15

Found - Orig. 13" now 24" W.Oak bears N.65°W., 11.9 ft. This BT has been opened years ago, old face & center rotted, no scribing found.
Orig. 6" now 10" W.Oak snag, S.60°E., 19.8 ft. scribing visible on old face "BT".
Set Brass cap at cor. mkd: County Surveyor's Office, 1958
¼ S23/S26 T28S R7W
New BTs -17" R.Fir S.12°W.,13.4 ft. scribed ¼ S26 CS BT.
17" R.Fir N.50°W.,18.2 ft. scribed ¼ S23 CS BT.

Doug. County Surveyors Office - John M. Powell; W. Penley Nov. 18, 1970 - C.S. File 54/113-18

Found - 1958 County brass cap, properly marked.
17" now 19" R.Fir, S.12°W., 13.4 ft., face grown over.
17" R.Fir stump bears N.50°W., 18.2 ft. shows good scar.
New BT - 18" Laurel N.7°E., 44.9 ft. scribed "¼ S23 CS BT".

Fd. OK by C. Sweeden, April 1999 - M131-42