

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5759)</p> <p>-----</p> <p>Set quar. sec. post, at average dist., from which A W.Oak 15" dia., bears S.77°E., 240 lks. A W.Oak 6" dia., bears N.88°E., 260 lks. dist.</p>
<p>F.C. Frear, 1917, Field Book 44 Page 17</p> <p>-----</p> <p>I find two witness trees as noted below: W.Oak 15" dia., bears S.77°E., 240 lks. My measurements, S77°E., 233 lks., tree marked. W.Oak 6" dia., bears N.88°E., 260 lks. My measurements, N.88°E., 269 lks., tree marked. I set a 6" x 6" x 14" sandstone with a cross mkd in the top.</p>
<p>Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - April 27, 1961 - C.S. File 49/50-49</p> <p>-----</p> <p>Found - Rock with cross as recorded by Frear in 1917. W.Oak, now 30", S.77°E., 153.8 ft., as recorded by Frear. Cut open old scar & found good scribing "¼S". W.Oak, down & dead, N.88°E., 177.5 ft. as recorded by Frear. Did not find scribing, tree badly rotted. Alongside rock set by Frear, Set Iron Pipe with brass cap mkd: County Surveyor's Office, 1961, T28S R7W ¼ S14 S23. Blaze & scribe new trees as follows: 20" Cedar N.31½°E., 85.8 ft. mkd. "¼ S14 CS BT". 10" B.Oak N.31°W., 34.7 ft. mkd. "¼ S14 CS BT". No trees handy in Section 23.</p>
<p>Doug. Co. Surveyors Office - Gary L. Langlitz, Deputy - S. J. Flause; Gorda Taylor - Feb. 24, 1977 - C.S. File 59/29-33</p> <p>-----</p> <p>Found - Sandstone set by Frear <u>not found</u>. 1961 DCSO brass cap found lying on the ground. The only remaining orig. BT, an Orig. 15" now 25" W.Oak, previously opened by Byron, pieces of wood with illegible reverse scribing found near base of BT, bears S.77°E., 153.8 ft. (Rec. S.77°E., 158.4 ft.) A 20" now 23" I.Cedar with scribing "¼ S14 CS BT" visible on an unhealed single blaze, bears N.31½°E., 85.8 ft. A 10" now 12" B.Oak, alive & well healed bears N.31°W., 34.7 ft. (Cont. Next Page)</p>

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 and 23

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Set - We add the markings "RESET 1977" to the brass cap previously marked, and set the monument 22" in the ground at the position determined by Frear as being the best position to resolve the conflicts he noted in the distances to the original bearing trees.