

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec Cor 25, 26, 35 & 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5751)

Set post, cor. of secs. 25, 26, 35 and 36, from which
A W.Oak 30" dia., bears N.10°E., 1006 lks. dist.
A W.Oak 20" dia., bears N.60°W., 65 lks. dist.
A B.Oak 15" dia., bears S.5°W., 695 lks. dist.
A B.Oak 20" dia., bears S.8°E., 750 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov. 7, 1958 - C.S. File 49/50-7

Found - Orig. 15" now 36" B.Oak, S.5°W., 458.7 ft. I find this dist. should be S.3°W., 445.7 ft., previously opened, shows good scribing "S BT".
30" W.Oak shows old scar, I open center, rotted, no scribing found. I believe this to be the orig. N.60°W., 42.9 ft. BT. (See statement by A. Boyer in C.S. File 49/50) I use this BT to determine position of corner.

Set Brass cap at cor. mkd: S26|S25 T28S R7W County Surveyors
S35|S36 Office, 1958

New BTs -10" W.Oak N.84°W., 4.4 ft. scribed T28S R7W S26 CSBT
8" B.Oak S.51°W., 46.9 ft. scribed T28S R7W S35 CSBT
13" W.Oak N.89°E., 12.8 ft. scribed T28S R7W S25 CSBT
13" W.Oak S.65°E., 13.7 ft. scribed T28S R7W S36 CSBT
Fence Corner bears N.9°W., 7.0 ft.

Found OK, O.S.H.D., Feb.8, 1985, C.S. File 63/9-4

Bruce Shaner, for R.Chasm, July 1997 - M 127-22; CS 65/15-5A

Found - 2½" DCSO 1958 Brass cap on a badly bent 1" iron pipe.

30" W.Oak BT w/face, bears N.60°W., 42.9 ft.
16" W.Oak BT w/face, bears N.84°W., 4.4 ft.
12" W.Oak BT w/face, bears S.51°W., 46.9 ft.
16" W.Oak BT w/face, bears N.78°E., 12.8 ft.
(rec. N.89°E.)
18" W.Oak BT w/face, bears S.75°E., 13.7 ft.
(rec. S.65°E)

New Accessory - Set a 6 ft. steel fence post, North 1.0 ft.
Note - at 4 way fence corner (±), some 300 ft. off Hoover Hill Rd.

(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25, 26, 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Douglas County Surveyors Office - Randall Smith & Stephen Flause - June 21, 1997 - C.S. 64/75-29</p> <p>-----</p> <p>Mon. FD.- 2½" dia. brass cap on a 1½" o.d. iron pipe protrudes 13" above ground. BC/IP is badly bent with top being NW'ly of plumb.</p> <p>Bt's Fd.- found as noted in 1997 Shaner renewal</p> <p>Mon. Set- Plumb position of bent BC/IP is referenced. BC/IP is straightened measures 36" long and returned to referenced position.</p>
<p>Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCS0 records Vol. 52 Page(s) 20002)</p>