

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5751-52)

-----  
Set qtr. sec. pst, from which  
A B.Oak 10" dia., bears S.11°W., 125 lks.  
A B.Oak 8" dia., bears N.40°E., 75 lks.

G. G. Stewart, Deputy - Wit: C. Crocker; V. Johnson - Oct. 1922 - C.S. File 5/25; M 5-70; Vol. 3 Pg. 125

-----  
Set Iron pipe from O.B.T. Marked:  
B.Oak 18" dia., bears S.11°W., 82.5 ft. (Orig. BT.)  
W.Oak 12" dia., bears N.34°E., 5.8 ft.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage; V. Perron - Sept. 1968 - C.S. File 52/79-36

-----  
Found - 1/2" I.P. and BTs as recorded by Stewart.  
18" now 24" B.Oak, alive, S.11°W., 82.5 ft., shows good scar. We do not open.  
12" now 20" W.Oak, alive, N.34°E., 5.8 ft. shows good scar.  
Set Brass cap at cor. mkd: County Surveyor's T 28 S R 7 W Office, 1968 ¼ S 26 S 25  
New BTs -7" D.Fir S.82°E., 18.7 ft. mkd. "¼ S25 CS BT".  
9" Laurel S.74°W., 16.7 ft. mkd. "¼ S26 CS BT".  
Corner lies at fence corner, fences N-E-W.

Found OK, Donald Bentz, Feb. 1983  
Found OK, O.S.H.D., Feb. 8, 1985, C.S. File 63/9-5