

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5752)

Set a post, cor. of secs. 23, 24, 25 and 26, from which
A W.Oak 16" dia., bears S.10°E., 144 lks.
A W.Oak 14" dia., bears N.80°E., 186 lks.
A W.Oak 14" dia., bears N.14°W., 202 lks.
A W.Oak 18" dia., bears S.73°W., 62 lks.

G. G. Stewart, Deputy - Witn: C. Crocker; V. Johnson - Oct. 1922 - C.S. File 5/25; Vol. 3 Pg. 125; M 5-70

Set Iron pipe from O.B.Ts. Marked:
B.Oak 8" dia., bears N.42°15'W., 31.2 ft.
W.Oak 6" dia., bears S.54°W., 32.5 ft.
W.Oak 8" dia., bears S.41°E., 27.5 ft.
W.Oak 14" dia., bears N.80°E., 122.8 ft. (OBT)

Doug. County Surveyors Office - Vernon Tracy; J. Heritage; V. Perron - Sept. 1968 - C.S. File 52/79-38

Found - Old squared post, no trace of I.P. called for by Stewart.
8" B.Oak now down & rotted, N.42¼°W., 31.2 ft., no scribing found.
6" now 10" W.Oak alive, S.54°W., 32.5 ft., open & find scribe. Rescribed: "T28S R7W S26 CS BT."
8" now 16" W.Oak, alive, S.41°E., 27.5 ft. shows good scars. We do not open.

14" now 20" W.Oak alive, N.80°E., 122.8 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyor's T 28 S R 7 W
Office S 23 | S 24
1968 S 26 | S 25

New BTs -6" W.Oak N.18°W., 12.2 ft. mkd: T28S R7W S23 CSBT
13" W.Oak N.56°E., 23.6 ft. mkd. T28S R7W S24 CSBT
Corner lies 3.0 ft. South of old E-W fence line.