

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5753)

Set post, cor. of secs. 13, 14, 23 and 24, from which
A B.Oak 12" dia., bears S.75°E., 20 lks. dist.
A B.Oak 12" dia., bears N.17°E., 13 lks. dist.
A B.Oak 8" dia., bears N.80°W., 40 lks. dist.
A B.Oak 16" dia., bears S.33°W., 22 lks. dist.

H.L. Eppstein, Wit: Robert Belt; Leroy Howard - July 1923 -
(No record source found. See "old" corner book, Page 111)

Set 4" x 4" x 3 ft. post from old BT., rotten but scribe marks visible. Marked new trees as follows:
W.Oak 20" dia., bears N.5°E., 40.0 ft.
B.Oak 12" dia., bears S.89°E., 35.7 ft.
B.Oak 10" dia., bears S.24°30'W., 24.3 ft.
B.Oak 8" dia., bears N.75°W., 49.4 ft.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov./Dec. 1958 - C.S. File 49/50-20

Found - All four of Eppstein's BTs as recorded except 20" W.Oak, record, N.5°E., 40.0 ft. should be N.55°E., 40.0 ft. I open & find good scribing. Also open record 8": B.Oak, should be 8" R.Fir, now stump, shows good scribing N.7°W., 49.4 ft. Also record 10" B.Oak should be 10" Fir, S.24½°W., 24.3 ft., shows good scars. I do not open. I open 12" now 16" B.Oak, S.89°E., 35.7 ft. & find good scribing.

Set Brass cap at cor. mkd: $\begin{array}{c|c} S24 & S13 \\ \hline S23 & S24 \end{array}$ T28S R7W County Surveyor's Office, 1958.

New BTs -14" Cedar bears N.60°W., 82.0 ft. scribed S14 T28S R7W CS BT.

15" Fir bears S.64°E., 40.7 ft. scribed S24 T28S R7W CS BT.

9" W.Oak bears N.17½°E., 53.1 ft. scribed S13 T28S R7W CS BT.

I find 1½" Iron pipe said by Cleal Davis to have been set for this section corner about 3 years ago, bears N.16½°E., 61.7 ft.