

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5753)

Set qtr. sec. post, from which
A B.Oak 14" dia., bears N.82°W., 225 lks. dist.
A B.Oak 8" dia., bears N.64°E., 153 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - April 1961 - C.S. File 49/50-42

Found - B.Oak now 30", N.64°E., 101.0 ft. This tree previously opened & center rotted. Fragments of scribe mkd. in rotten wood found inside.
B.Oak now 40", N.82°W., 148.5 ft. This tree previously opened & center rotted. No scribing found.

Set Iron pipe with Brass cap mkd: County Surveyors Office
1961 T28S R7W ¼ S14|S13
New BTs -14" B.Oak S.57°E., 27.0 ft. mkd. ¼ S14 CS BT.
12" W.Oak N.88½°W., 79.1 ft. mkd. ¼ S13 CS BT.
Corner lies in N and S. fence line. Fence corner, N-S-W., bears North approx. 40 ft.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/29/1998 - C.S. File 66/2-19

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 14" above ground, in a N-S fence line, properly marked. 1961
14" now 40" dia., down & rotted B.Oak near rec. "N.82°W., 148.5 ft." OBT
8" now 26" dia., nearly dead B.Oak with a previously opened unhealed rotted blaze, bears N.64°E., 101.0'. (Agrees w/rec.) OBT
14" now 18" dia., B.Oak with a fully healed double blaze, bears S.60°E., 26.4' (Rec. S.57°E., 27.0')
12" now 17" dia., W.Oak with a fully healed double blaze, bears S.88½°W., 78.16' (Rec. N.88½°W., 79.1', possibly read bearing wrong in 1961)
New BTs- 16" dia., Madrone, double blazed and scribed "¼ S13 CS BT" bears S.77°E., 45.9'.
6" dia., D.Fir, double blazed and scribed "¼ S14 CS BT" bears N.56½°W., 83.0'.

Fd. OK by D. Edwards, Dec. 1999 - M134-11