TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5751)

Set qtr. sec. post, from which
A W.Oak 20" dia., bears N.10°W., 40 lks.
A B.Oak 18" dia., bears S.42°W., 87 lks.
Richardson's house bears N.25°W., 3.51 chs.

Doug. County Surveyors Office - James W. Byron, Deputy - M. Godfrey; S.A. Bilow - Nov. 17, 1958 - C.S. File 49/50-12

Found - W.Oak N.10°W., 26.4 ft., now 30" dia., chopped open and found reverse scribing "¼ S BT".
Oak, S.42°W., 57.4 ft., down & rotted too badly to find any trace of scribing.
AT cor. set, Iron pipe with brass cap mkd: "County Surveyors Office, 1958, T28S R7W ¼ S25/S36
and blaze & scribe the following BTS:
16" Fir N.82°E., 37.6 ft. mkd. "¼ S25 CS BT."
8" W.Oak S.21°W., 6.0 ft. mkd. "¼ S36 CS BT."

Doug. County Surveyors Office - Randall Smith, P.L. Bair - Dec. 5, 1983 C.S. File 62/9-18

Found - 1958 DCSO brass cap on 1½" I.P. protruding 13½" above ground. Cap properly mkd.
Orig. 20" W.Oak now 30" dia., hollowed out, tree still alive. No scribing visible, bears N.10°W., 26.4 ft.
Orig. 18" B.Oak now a depression in the ground, no remains of BT, bears S.42°W., 57.4 ft.
16" now 22" dia., Fir stump, 4½ ft. high, with well healed double blaze, bears N.82°E., 38.1 ft. (Rec. 37.6 ft.)
8" W.Oak now 9" dia., with well healed double blaze, bears S.21°W., 6.0 ft.
New BTs -10" B.Oak double blazed & scribed "¼ S36 CS BT" bears S.59°., 44.5 ft.
10" D.Fir double blazed & scribed "¼ S36 CS BT" bears S.75°W., 19.5 ft.
Corner lies 5 ft. south of east-west fence line on a small knoll approx. 1000 ft. south of State Hwy. #42.

Fd. Ok, 4/29/2011 by ODOT - St. Hwy 42-015C