

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5753)

Set qtr. sec. post at proper dist., from which
A B.Oak 14" dia., bears S.7°E., 11 lks.
A B.Oak 10" dia., bears N.84°E., 29 lks.

Max H. Hull, L.S. #901, For: Bob Griffis - April 23, 1982 - M 92-4 and C.S. File 58/179

Set - 5/8" x 30" Iron rod, with plastic cap mkd. RS 901, from one orig. BT.
Found - 20" B.Oak stump (hollow) with a scribe negative, bears S.7°E., 7.26 ft.
New BTs - 24" B.Oak bears S.57°E., 18.0 ft.
10" Madrone bears N.85°W., 17.48 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/5/2002 - C.S. File 66/48-1

Found - 1982 5/8" iron rod with plastic cap protrudes 3" out of ground. I.R. fd. 0.8 ft. South of an E-W fence line.
14" now rotted to ground Oak scribing found root hole bears S.7°E., 7.3 ft. (OBT)
24" now 27" dia., B.Oak nearly dead with a partially healed rotted double blaze. Partial scribing visible "¼S" bears S.57°E., 18.0 ft. (1982)
10" now 13" dia., Madrone bark scribing visible "¼ S13 BT" bears N.85°W., 17.5 ft. (1982)
New - Intersection of E-W+S'ly fence line is East 34.5 ft.
13" dia., D.Fir double blazed & scribed "¼ S13 CS BT" bears N.16°W., 34.6 ft.
16" dia., D.Fir double blazed & scribed "¼ S24 CS BT" bears S.88½°E., 33.5 ft. (Note: BT at fence corner.)
13" dia., D.Fir double blazed & scribed "¼ S24 CS BT" bears S.41½°W., 59.0 ft.
Compass decl. 17½°E.

Fd as per record, 7/2024, N Hibbs - M183-80