TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor for secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5755)

Set quar. sec. post at average dist., from which
A B.Oak 10" dia., bears N.89°E., 990 lks. dist.
A B.Oak 12" dia., bears S.13°E., 365 lks. dist.
Edward and James F. Shiffields' house bears N.45°W.

F.C. Frear, Deputy Co. Surveyor - Geo. Bacon; E.F. Ollivant; Jan. 5, 1917 - Vol. 3 Pg. 48 and 36; Field Book 43 Pages 45 and 49-50; C.S. File 5/24

Renew corner from old Gov't BTs. Set in a 1½" x 30" Iron rod, from which
A 30" B. Oak bears S.13°E., 3.65 chs.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - March 1961 - C.S. File 49/50-41

Found - Orig. 12" now 44" B.Oak S.13°E., 240.9 ft. shows good scribing "BT".
Orig. NE BT not found.
Corner in field - set Wit. Cor. 140 ft. South.
Set Brass cap at Wit. Cor. mkd: "Wit. C. 140 North to ¼ S 1/S12
T28S R7W
County Surveyor's Office 1961
Iron bar set in 1917, not found.
New BTs -18" B.Oak bears S.56°E., 86.4 ft. scribed ¼ S12 CS BT W.C.
9" B.Oak bears N.74°W., 47.1 ft. scribed ¼ S1 CS BT. W.C.

Fd. OK by D. Edwards, Dec. 1999 - M134-11