

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 1

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records Vol. 12 Page(s) 5219)

-----  
Set ¼ sec. post, made a trench and drove a charred stake 12 ins. long, in the center, as per instructions.

GLO survey by F. Mensch, Contract #109 dated 1924 (DCSO records Vol. 14 Page(s) 5865)

-----  
Point for standard ¼ sec. corner, located by Hathorn's record tie from the ¼ sec. cor. of sec. 36.  
At the exact corner point  
Set an iron post, 3 ft. long, 2 ins. dia., 28 ins. in the ground, for standard ¼ sec. corner, with brass cap mkd:

CS ¼ S1  
1924

From which;

An Ash, 10" dia., bears S.64°W., 61 lks., mkd: SC ¼ S1 BT.

No other tree available and no stones available for mound.

Hathorn's ¼ sec. cor. of sec. 36 bears S.87°43'W., 7.5 chs.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/5/1998 - C.S. File 66/2-21

-----  
Found - 2½" dia., brass cap on a 1" O.D. iron pipe, protrudes 10" above ground, properly marked. 1924 GLO

10" now 12" dia, Ash with a fully healed single blaze illegible scribing vis., bears S.64°W., 40.3', agrees w/rec. 1924 GLO

New BTs- 10" dia., Ash double blazed and scribed "¼ S1 CS BT bears S.53°E., 2.0'.

6" dia., Ash single blazed low and scribed "X CS BT" bears N.6°W., 13.5' (Note: tree not in Sec. 1)