

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36: & 31 of T28-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5696)

Set ¼ sec. post, from which
A Y.Oak 36" dia., bears N.20¼°W., 490 lks. dist.
A Y.Oak 12" dia., bears S.43½°E., 119 lks. dist.

G.G. Stewart; Wit: J. Lewis; J.M. Lamb - Jan. 12, 1922
Vol. 3 Page 109; "old" corner book, page 109

Set Iron bar for corner.
Fir 10" dia., bears N.6½°E., 45 ft.
Laurel 8" dia., bears S.71°W., 17.5 ft.
Corner reset from 1 original BT.

Doug. County Surveyors Office - James W. Byron - May 24, 1961
C.S. File 49/50-59

Found - 5/8" Bolt at corner.
10" now 16" Fir snag N.6½°E., 45.0 ft. We open and
find good scribing "S".
8" now 12" down Laurel S.71°W., 17.5 ft.
No trace of original BTs found.
Set brass cap at cor. and alongside 5/8" bolt and marked:
County Surveyor's Office, 1961 ¼ S36 | S31 T28S
R7W R6W
New BTs - 9" W.Oak bears N.60°W., 12.4 ft. scribed ¼ S36 CSBT
10" Laurel bears S.60°E. 29.8 ft. scribed ¼ S31 CSBT
N-S fence is 32 ft. West of corner.

Fd. and used, BLM subdivision of sec. 31, T28-6, by Wayne Rogers under Group #1351 - Survey 1987 (DCSO records, Vol. 48 Pages 18441-42)