

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. 1 & 12; 6 & 7 of T28-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5693)

-----  
Set post cor. to sec. 1, 6, 7 and 12, from which  
A W.Oak 24" dia., bears N.20°E., 227 lks.  
A Y.Oak 20" dia., bears N.3½°W., 177 lks.  
A Y.Oak 16" dia., bears S.22°W., 121 lks.  
A Y.Oak 20" dia., bears S.17¼°E., 165 lks.

F.C. Frear - Geo. Bacon; E.F. Ollivant - Jan. 5, 1917 -  
Field Book 43 Pages 42-45 & 49-50; Vol. 3 Pg. 48 & 36;  
C.S. File 5/24

-----  
Renew from old BTs. Set in 12" x 12" x 18" sandstone,  
from which  
A W.Oak 36" dia., bears N.20½°E., 2.28 chs.  
A W.Oak 30" dia., bears N.3½°W., 1.78 chs.  
A B.Oak 24" dia., bears S.22°W., 1.21 chs.  
A B.Lak 30" dia., bears S.17¼°E., 1.65 chs.

Doug. County Surveyors Office - James Byron, Deputy - Milo  
Godfrey; S.A. Bilow - Nov/Dec. 1958 - C.S. File 49/50-21

-----  
Found - All BTs as recorded by Frear in 1917:  
36" W.Oak N.3½°W., 117.5 ft. now down & partly  
rotted. I find good scribing "BT".  
30" B.Oak S.17¼°E., 108.9 ft., now down.  
24" B.Oak S.22°W., 79.9 ft. shows scar, I do not  
open.  
36" W.Oak N.20½°E., 150.5 ft. shows scar, I do  
not open.

Find corner stone with + on top.  
Set brass cap alongside corner stone and marked:  
County Surveyors Office  
S 1 | S 6 T28S  
R7W S12 | S 7 R6W  
1958

New BTs- 12" W.Oak bears N.56°W., 23.2 ft. scribed S1  
T28S R7W CS BT.  
28" W.Oak bears N.25°E., 52.0 ft. scribed S6  
T28S R6W CS BT.  
10" W.Oak bears S.62°E., 35.9 ft. scribed S7  
T28S R6W CS BT.  
10" Laurel, S.32½°W., 50.5 ft. scribed S12 T28S  
R6W CS BT.

Found OK by D. Edwards, July 2002 - M140-49