

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903020

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 T27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, Under Contract #44 dated May 30, 1854 - (DCSO records, Volume 12 Page 5219)

-----  
Set sec. post, made a trench and drove a charred stake 12" long, in the center, as per instructions.

GL0 survey by Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 12 Page 5223 and Pg. 5231)

-----  
Set ¼ post, from which  
An Ash 15" dia., bears N.12½°E., 289 lks. dist.  
An Ash 18" dia., bears N.22°W., 362 lks. dist.

GL0 survey by Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 12 Page 5230)

-----  
Set Standard ¼ sec. post, deposited a boulder 6x10". Raised mound with trench as per instructions.

GL0 survey by F. Mensch, Under Contract #109 dated 1924 (DCSO records, Volume 14 Page 5837)

-----  
East along the S. Bdy of Sec. 36. No evidence is found, after careful search, of Hathorn's ¼ sec. cor. of sec. 36. Set temp. corner.

No evidence is found of Ford's ¼ sec. cor. of sec. 36.

-----  
(Same Deputy, same contract - DCSO records, Vol. 14 Pg. 5838)

-----  
At proportionate distance (39.95 chs.) Set an Iron post, 3 ft. long, 1" dia. m 27" in the ground, for ¼ sec. cor. of sec. 36 with brass cap mkd.

¼ S36  
1924

from which (new bearing trees)

An Ash 6" dia., bears N.53°E., 11 lks. dist., mkd. S36 BT.

An Ash 10" dia., bears N.10¼°W., 370 lks. dist., mkd. ¼ S 36 BT.

(Ford's standard ¼ sec. cor. of sec. 1, T.28-7 bears N.87°10'E., 7.50 chs. dist.)

(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903020

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 T27-7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-30

-----  
Found - Brass cap at corner. BTs not found.  
New BTs- 15" Ash bears S.84°E., 21.3 ft. scribed ¼ S36 CSBT.  
12" Ash bears N.86°W., 10.7 ft. scribed ¼ S36 CSBT.  
Corner is 4 ft. North of fence.

Found OK, June 1992 by R.Dolan - M117-32.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/5/1998 - C.S. File 66/2-20

-----  
Found - 2½" dia., brass cap on a 1" O.D. iron pipe, protrudes 5" above ground, properly mkd 1924 GLO  
15" now 19" dia., Ash with a partially healed double blaze scribing vis. "36", bears S.84°E., 21.3', (agrees w/rec.) 1961 DCSO  
12" now multi-trunked Ash with a partially healed double blaze on Easterly 16" trunk, scribing vis. "S3", bears S.77°W., 10.7' (Rec. N.86°W., 10.7') 1961 DCSO  
6" now cluster of newer Ashes at rec. bearing "N.53°E., 7.3 ft.". 1924 GLO  
1924 NW BT is gone.  
New B0s- South West tree of a cluster of Ashes double blazed and scribed "¼ S36 CS BT" on a 7" dia., trunk, bears N.60°E., 7.3' to center of base of scribed trunk.  
5/8" x 30" long iron rod with alum DCSO cap stamped "B0 1" is set in East-West fence line, protrudes 10" above ground, bears South 3.5'.