

PRIMARY CORNER DESCRIPTION Sec. Cor. Secs. 34 & 35 T27-7 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5223)

Set post, cor. secs. 34 and 35, deposited a stone 3x8x8" and raised mound with trench, as per instructions. Corner established by Ford, bears N.15°W., 76 lks. dist.

GLO survey by Fred Mensch, Under contract #109 dated 1924 (DCSO records, Volume 14 Page 5840)

Intersect the cor. of secs. 34 and 35, determined by the intersection of the very old rail fence lines, bearing N. & W., to which is joined the newer fence from the E. The fence to the W. is rotten and partially removed. The point agrees closely with the position by proportionate measurement and is accepted. At the exact cor. point, Set an Iron post, 3 ft. long, 2" dia., 26" in the ground, for cor., with brass cap mkd.

T27S R7W
S34|S35
1924

from which

A wild Apple tree, 5" dia., bears N.88¼°E., 170 lks. dist., mkd. T27S R7W S35 BT.

No bearing tree or other object available in sec. 34.

No stones available for mound.

The Ford standard cor. of secs. 2 & 3, re-established, bears N.84°53'E., 7.3 chains.

(The cor. established by Ford for cor. of secs 34 & 35, re-established as angle point, bears N.15°W., 76 lks.)

Cor. found and used, Glenn Baughman, April 1987, M 104-24

Fd. & used BLM resurvey by Philip G. Griffin, Cadastral Surveyor, under Group # 1529, surveyed April/July 1990 (DCSO Records Vol. 50 Page(s) 19136)

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/11/1998 - C.S. File 66/2-24

Found - 2½" dia., brass cap on 2" O.D. iron pipe, protrudes 6" above ground, properly marked. 1924

1998 DCSO BC/IP T 28 S R
S 3 S 2 7

agrees w/rec. "N.84°53'E., 481.8 ft." 1998

No BTs found.

(Cont. next page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903050

PRIMARY CORNER DESCRIPTION Cor. Secs. 34 & 35 only (S) T27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BOs - 5/8" I.R. with alum. cap stamped "BO 1" is set in North running fence line, protrudes, 3" above ground, bears North 10.0' 9" dia., Pear, single blazed scribed "X CS BT" bears N.59°W., 354.0'
Top of barn (Old Octagon shaped) bears N.5¼°W.
Corner lies at the intersection of fences running E-W and North. See sketch in file.

FD. OK by Raymond Brown - March 2001 - M 137-1