

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903110

PRIMARY CORNER DESCRIPTION Angle Point #6 (Sec Cor 4 & 5)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5230)

Set post, cor. of secs. 4 and 5, from which
An Oak 24" dia., bears S.9°W., 114 lks. dist.
A Laurel 20" dia., bears S.41°E., 16 lks. dist.

For Ford's Cor. for 4 & 5, see Vol. 12 Pages 5220-21

GL0 survey by Fred Mensch, Under Contract #109 dated 1924 (DCSO records, Volume 14 Pages 5846-47)

Intersect the cor. established by Hathorn for standard cor. of secs. 4 and 5, located by record bearing and distance from the original SE bearing tree, showing evidence of the old blazes, no marks found. The original SW tree is entirely gone.

At the exact cor. point, Set an Iron post, 3 ft. long 1" dia., 28" in the ground, for angle point, with brass cap marked
AP 6 S33
1924

from which (new bearing trees)
A Fir 14" dia., bears N.50°E., 29 lks. dist. mkd AP BT.
A Fir 14" dia., bears N.60°W., 7 lks. dist., mkd. AP BT.
The original SE bearing tree, a laurel 30" dia., bears S.41°E., 16 lks. dist.
The original position of the SW bearing tree, indicated by a stump hole, bears S.9°W., 114 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-35

(Angle Point #6)
Found - Iron pipe with brass cap mkd. "AP 6 1924".
14" Fir stump N.50°E., 19.1 ft., shows good scar.
14" Fir stump N.60°W., 4.6 ft. shows good scar.
30" Laurel S.41°E., 10.6 ft., tree now dead.
New BTs- 14" Fir S.63½°W., 25.8 ft. mkd: AP CS BT.
23" Fir S.87°E., 31.6 ft. mkd. AP CS BT.
Corner is 1 ft. North of new E & W fence.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 19999-20000)