

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903140

PRIMARY CORNER DESCRIPTION Angle point West from ¼ S. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5230)

-----  
Set Standard ¼ sec. post, from which  
An Oak 10" dia., bears S.60°W., 34 lks. dist.  
A Laurel 20" dia., bears S.40°E., 44 lks. dist.

1924 GLO resurvey by Mensch (DCSO records, Vol. 14 Pages 5848-49)

-----  
Intersect the cor. established by Hathorn for ¼ sec. cor. of sec. 5, located by measurement from the original bearing trees. The SW tree is an Oak, scribe marks legible. Blazes show on SE tree.

At the exact cor. point  
Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for angle point, with brass cap marked: AP  
1924

from which (New bearing trees)  
A Pine 8" dia., bears N.17°E., 20 lks. dist., mkd. AP BT.  
A Fir 14" dia., bears N.35°W., 38 lks. dist. mkd. AP BT.  
The orig. SE BT, A Laurel, 28" dia. bears S.40°E., 44 lks.  
The orig. SW BT, an Oak 16" dia., bears S.40°W., (instead of S.60°W.), 34 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb. March 1961 - C.S. File 49/79-36

-----  
Renew angle point (S.35°15'W., 5.39 chs. from W.P. for N. ¼ cor. Sec. 5.

Found - Brass cap at corner. No trace of SW BT. NW and NE BTs., stumps only. SE BT in good condition  
New BTs - 9" R. Fir bears N.29½°E. 26.2 ft. scribed AP CS BT  
Rescribe orig. now 32" Laurel, bears S.42°E. 29.3'.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20001)

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/6/1998 - C.S. File 66/2-22

-----  
Found - 2½" dia., brass cap on a 1" O.D. iron pipe, protrudes 4" above ground, properly marked. Leans 0.5' south easterly of plumb. 1924 GLO  
(Cont. next page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903140

PRIMARY CORNER DESCRIPTION Angle point West from ¼ S. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

20" now 30" dia., Madrone with an open rotted blaze, no scribing visible, and a fully healed double blaze bears S.40°E., 29.0 ft. Agrees w/rec. OBT  
14" D.Fir now rotted remains w/illegible scribing fd., bears N.35°W., 25.1', agrees w/rec. 1924  
8" Pine now rotted remains with illegible scribing found "T" bears N.14°E., 13.2' (Rec. N.17°E., 13.2') 1924  
9" now 18" dia., 1' high D.Fir stump, no marks vis., bears N.29½°E., 26.2' (Agrees w/rec.) 1961 (Note: stump is solid)  
Reset - BC/IP is returned to plumb position, protrudes 4" above ground.  
New BTs- 9" dia., D.Fir, double blazed and scribed "AP CS BT", bears N.2°W., 15.3'.  
5" dia., D.Fir, double blazed and scribed "AP CS BT", bears S.1½°W., 8.2'.  
Corner lies in an E-W fence line.