TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 903190

PRIMARY CORNER DESCRIPTION So. ¼ Cor. Section 31 only, T27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy under Contract #57 dated April 12, 1855 (DCSO records, Volume 12 Page 5225)

Set ¼ sec. post, from which
A W.Oak 15" dia., bears N.25°W., 18 lks. dist.
A W.Oak 15" dia., bears S.26°W., 18 lks. dist.

GLO survey by Fred Mensch under Contract #109 dated 1924 (DCSO records, Volume 14 Pages 5852-53)

Intersect the ¼ sec. cor. of sec. 31, located by measurement from the original bearing trees, old blazes plain, but marks rotted away. At the exact cor. point, Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec.cor. of sec. 31 only, with brass cap marked: ¼ S31 / 1924

from which (old bearing trees)
A W.Oak now 22" dia., bears S.26°W., 18 lks. dist., old blaze opened, not remarked.
A W.Oak now 22" dia., bears N.25°W., 18 lks. dist., old blazed opened, not remarked.

H.L. Eppstein - Wit. B. Lane; Bob Mathews; Fritzpatricks Bros. June, 1930 - M 1-73; C.S. file 14/59

Standard Government pipe set by Mensch, U.S. Surveyor.
I marked new witness trees as follows:
A Fir 10" dia., bears S.75°E., 20.3 ft.
A W.Oak 24" dia., bears S.56°30'W., 46.5 ft.

Doug. County Surveyors Office - James W. Byron, Deputy; Milo Godfrey; Clete Putnam - Feb. 1961 - C.S. File 49/79-33

Found - Brass cap.
Both original BTs and Eppstein's SW BT.
New BTs - 6" W.Oak bears N.25°E., 29.6 ft. scribed ¼ S31 CSBT
8" W.Oak bears N.67½°W., 44.9 ft. scribed ¼ S31 CSBT