

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 040020

PRIMARY CORNER DESCRIPTION NW Cor. R.M. Gurney DLC #40

Alias 041050 Description Int SE Cor. Weekly DLC #41

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

DLC Survey by J.A. Burnett, under Contract #75 dated Dec. 19, 1856 - (DCSO Records, DLC Volume Page 521 and Pg.522  
-----

(Page 521)

Set a post, from which

A W.Oak 12" dia., bears S.65°E., 1126 lks. dist.

(Page 522)

Set a post, from which

A W.Oak 8" dia., bears S.70°W., 167 lks.

A.R. Evans - Wit: J.E. Clinton - Dec. 1951 - M 9-41  
-----

Set by proper measure from Cole survey in 1915 (Vol 2 Pg. 268) and record tie in original govt. field notes, from ¼ cor. sec. 15 and 22 to West line of Claim & SW cor. DLC 41 (found)  
Set 5/8" iron rod for corner. Blazed and scribed BT:

24" Locust S.19°E., 95.0 ft. mkd. "N.W. Corner Claim 40  
BT"

Douglas Co. Surveyors Office - John M. Powell, and crew -  
March 1966 - C.S. File 52/79-20  
-----

Found - 24" Locust, now 30", S.19°E., 95.0 ft., faint scribe visible "NW 40".

No trace of iron rod at corner.

At DLC Corner, Set Iron bolt with 1" square head 20" long.

Reblazed and rescribed:

30" Locust S.19°E., 95.0 ft. scribed "NW DLC #40 CS  
BT"

The NE. corner of Rodger Iverson's porch bears S.68°W., 189.3 ft. Corner is about 6" under ground and 3.6 ft. East of N-S fence.

Fd. OK, Dec. 1992 by D. Bentz - M 116-57

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 6/6/2001 - C.S. File 66/21-24  
-----

Found - Iron bolt with 1" square head bent 5" east of plumb, flush with ground. (1966) Iron bolt measured 24" long is straightened & returned to plumb position, set 6" below ground in a N-S fence line.

From iron bolt

1951 SE BT gone.

NE corner of Iverson house porch, bears S.68°W., 189.3 ft. (1966)

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 040020

PRIMARY CORNER DESCRIPTION NW Cor. R.M. Gurney DLC #40

Alias 041050 Description Int SE Cor. Weekly DLC #41

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

From New corner based on found OBT

12" now 26" W.Oak, previously opened rotted search area, we open lower & find good reverse scribing "BT". Tree is alive (orig. BT NW cor. DLC 40) bears S.63°E., 743.2 ft.

Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at a position determined by orig. BT, 3" below ground. (Bearing taken to OBT determined by GPS agrees closely with staff compass) Brass cap mkd:

DOUGLAS COUNTY SURVEYORS

T28S

R DLC

8 41|NW 40

W 2001

1966 iron bolt bears N.70½°W., 20.5 ft.

26" dia., Apple single blazed low & scribed "NW DLC 40 BT", bears N.11½°E., 200.0 ft.

29" dia., Locust single blazed & scribed "NW DLC 40 CS BT" bears S.3½°E., 167.7 ft.

USC&GS brass cap/con. monument "Q344 1942" bears N.82 3/4°W., 172.9 ft.

Note - See C.S. file 66/21-24 PG 2 for sketch.

See C.S. File 66/21-24 PGs 4-14 (11 pgs) for GPS print outs.