

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 041020

PRIMARY CORNER DESCRIPTION NW Cor. Wm. Weekly DLC #41

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

DLC Survey by J.A. Burnett, under Contract #75 dated Dec. 19, 1856 - (DCSO Records, DLC Volume Page 523)

-----  
Set a post, from which  
A Fir 30" dia., bears S.53°E., 31 lks.

F.J. Cole, Deputy - Wit: Chas. Wilson; S.A. Gurney; J.W. Gurney - Jan. 1915 - Vol. 2 Pg. 268; Field Book 37 Pgs. 2-5; (and "old" cor. book Pg. 116)

-----  
Renew corner from original tree which is dead.  
Marked - A Fir 12" dia., S.79°45'E., 68 lks.

Douglas County Surveyors Office - James W. Byron - March 3, 1970 - C.S. File 52/79-41

-----  
Corner searched for, not found.  
Probably taken by power line R/W.

BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18408)

-----  
Point for the NW. cor. of DLC #41, at proportionate position, determined by the Grant boundary method; there is no remaining evidence of the original corner.

Set a stainless steel post 28" long, 2½" dia., 26" in the ground with brass cap mkd.

T 28 S R 8 W  
S 15 | C 41  
1987

from which

A W.Fir 30" dia., bears N.15 3/4°E., 35 lks. dist. mkd. C 41 BT.

A Fir 17" dia., bears S.49°E., 36 lks. dist. mkd. C41 BT.  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.