

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 041030

PRIMARY CORNER DESCRIPTION SW Cor. Wm. Weekly DLC #41

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Dec. 19, 1856 - (DCSO Records, DLC Volume Page 523)

Set a post, from which
A Fir 12" dia., bears N.40°E., 16 lks.

F.J. Cole, Deputy - Wit: Chas. Wilson; S.A. Gurney; J.W. Gurney - Jan. 1915 - Vol. 2 Pg. 268; Field Book 37 Pgs. 2-5 (and "old" Renewal Vol. 1 Pg. 116)

Fd tree in place and renew cor. With fir post, mkd: C41 DCS

A. R. Evans - Wit: J.I. Clinton - Dec. 1951 - M 9-41

Set by proper measure with Cole Survey. (1915)
Set 3/4" iron pipe for corner, blazed and scribed BTs:
30" Fir N.60°E., 17 ft.
12" Fir S.54°W., 8.0 ft.
Both marked S W CL. 41 R.E. 2741 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - March 1966 - C.S. File 52/79-19

Found - 1/2" Iron pipe at corner.
12" D.Fir now 14", S.54°W., 8.0 ft. scribe visible "W".
30" Fir stump, N.68°E., 17.0 ft. scribe visible "W" "41".
New BT - 8" W.Fir N.15°E., 13.3 ft. scribed SW DLC #41 CS BT.
Corner lies about 60.0 ft. South of creek.

BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18407-08)

The SW. cor. of DLC #41, perpetuated and recorded by Cole in 1915, from original evidence no longer in existence, reestablished and recorded by Evans, in 1951, using Cole's record; subsequently perpetuated and recorded by Powell in 1966, monumented with an iron pipe 1/2" dia., firmly set, projecting 4" above ground, from which the remains of bearing trees mkd. by Evans:

A sawed Fir stump 30" dia., bears N.60°E., 26 lks. dist., with healed blaze.

A Fir 16" dia., bears S.56°W., 12 lks. dist. with healed double blaze.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 041030

PRIMARY CORNER DESCRIPTION SW Cor. Wm. Weekly DLC #41

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a bearing tree mkd. by Powell

A W.Fir 10" dia., bears N.17°E., 18 lks. dist. with frag-
mentary scribe marks visible on partially healed blaze.

At the corner point

Set a stainless steel post 28" long, 2½" dia., 24" in the
ground, directly over the iron pipe, with brass cap mkd.

T 28 S R 8 W
S 15 | C 41
1987

Deposit white "DEEP-1" magnetic marker at base of stainless
steel post.